



**Specification:**  
 1. Electrical Char  
 Insulation Resistance: 500MΩ min. 500V DC for 1 minute  
 Contact Resistance: 20mΩ max.  
 Rating Current: 1.5A max.  
 Rating Voltage: 120V AC  
 Dielectric Voltage: 1000 Vrms at 1MA 60 sec. min.

2. Physical Char  
 Housing: PBT Glass filled (UL 94V-0) Color: Black  
 Soldering Temperature: 235°C for 5 sec.  
 Spring Wire: 0.45mm Dia Phosphor Bronze  
 6u" Gold plating over Nickel  
 Temperature Range: -40°C to +85°C  
 Durability: 500 mating cycles min.

3. Packing: Tray

**RoHS compliant**  
 Unit:mm

Scale	Free								
TOLERANCE									
.XX	±0.20								
.XXX	±0.13								
.XXXX	±0.05								
DIM	TOL								
Angle	+0°30'								

Customer-No.	Name	Date	Name	Date	Name
	Winnie	04.08.2016	Winnie	04.08.2016	Winnie
ASSMANN WSW-No.					
A-2014-0-4-N-T-R					
Drawing-No.					
ASS 7326 CO					
Replace					

1	2	3	4	5	6	7	A
1	2	3	4	5	6	7	B
1	2	3	4	5	6	7	C
1	2	3	4	5	6	7	D
1	2	3	4	5	6	7	E
1	2	3	4	5	6	7	F
1	2	3	4	5	6	7	G
1	2	3	4	5	6	7	H



ASS 7326 CO rev00

SHEET