## 24 INCHES LENGTH



Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink

## Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Connector B	Connector A			Cable			Connector B		
90° 45° 0° 225° 278° 315° Connector A	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	132245 SMA R/A BHD Jk 50O SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear I Brass Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Right A		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 24 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	132245 SMA R/A BHD JK R 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mo Brass Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Right Ang 0°		
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT DO NOT CODY CUSTOM CABLE			THIS DRAWING MAY CONTAIN PROPRIETARY INFORMATION / FOR ANY PURPOSE DETRIMEN INC. IT MAY NOT BE REPRODUU IN ANY FORM WITHOUT THE W CUSTOM CABLE INC. ACCEPTA ESTABLISHES AND AGREEMEN	AND MUST NOT BE U TAL TO CUSTOM CAI CED OR TRANSCRIBI /RITTEN CONSENT O .NCE OF THIS DRAWI	BLE ED F NG Part No:	SMA-RA-JK/SMA-RA-JK G174 24I		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	