24 INCHES LENGTH



Connector A 132245 SMA Jack Right Angle Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 132119 SMA Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

Right Angle	Connector A			Cable			Connector B		
90° 45° 90° 90° 90° 90° 90° 90° 90° 90° 90° 90	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	132245 SMA R/A BHD JK RG174 RG316 LMR100 500 SMA Jack Right Angle Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Right Angle		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 24 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Material: Body Finish: IP Rating: Contact Material: Contact Tinish: Max. Freq.: Booting: Clocking:	132119 SMA BHD JK RG17 SMA Jack Straight Solder Standard 50 Ohm Bulkhead - Rear Mo Brass Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Straight B 0°		
AmphenolTHIS DRAWING MAY CONTA PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIME INC. IT MAY NOT BE REPROD IN ANY FORM WITHOUT THE CUSTOM CABLE INC. ACCEPT ESTABLISHES AND AGREEME			AND MUST NOT BE USED TAL TO CUSTOM CABLE CED OR TRANSCRIBED WRITTEN CONSENT OF NCE OF THIS DRAWING Part No:			G174 24I			