



MODULAR JACKS AND PLUGS: GDx Series

Right Angle Modular Jack

Product Features

- 0.595" Height
- Snap-In Board Retention Tabs
- Panel Stops Available
- Available in 4, 6 and 8 Position Housings
- CSA/NRTL Certified File No. LR78160
- UL File No. E134345

Performance Specifications

Materials and Finish

Housing Material

PBT Thermoplastic, UL 94V-0 Rated, Black Color

Contact Material

Phosphor Bronze

Electrical Characteristics

Insulation Resistance

500 Megohms Min.

Dielectric Withstanding Voltage

1000V AC for 1 Minute

Contact Resistance

20 milliohms Max.

Current Rating

1.5A

Voltage Rating

125V DC

Operating Temperature

-40°C to +85°C

Generated Part Number

GDx-A-44

Part Number Builder

GDx	-	A	44		
Series		Panel Stop	Positions & Contacts	Keyed Option	Plating Option

Series

GDx - Right Angle Modular Jack

Panel Stop

A - With Panel Stops
N - Without Panel Stops

Number of Positions / Contacts

44 - 4 Positions / 4 Contacts (only with Panel Stop)
64 - 6 Positions / 4 Contacts
66 - 6 Positions / 6 Contacts
88 - 8 Positions / 8 Contacts

Keyed Option

- Not Keyed
 - Keyed (Only for 8P8C)

Plating Option

- Gold Flash
 - 50µ" Gold Plating

Contact Kycon for High Temperature and Other Options.

GDx Series

Dimensions in mm

GDx-A-44

