



CIRCUIT 3 POSITION

NOTES:

1. ALL DIMENSIONS IN MM
2. GENERAL TOLERANCE: X.X=±0.4  
X.XX=±0.25
3. TERM. NOS. FOR REFERENCE ONLY.
4. CONTACT RATINGS: 25mA @24VDC. (Switch)  
100mA @50VDC. (Carry)
- ▲ 5. CONTACT MATERIAL:  
CONTACTS: (MOVABLE) Copper w/Gold Plate  
TERMINALS: BRASS w/Gold Plate
6. INSULATION RESISTANCE:  
100 Mega-ohms min. @500VDC
7. CONTACT RESISTANCE:  
50 MILLI-ohms typical @2-4VDC @100mA
8. OPERATING TEMP.:  
-40°C to +80°C
9. PACKAGE: IN DISPENSING TUBES  
WITH ALL POLES IN THE "OFF" POSITION.

RECOMMENDED P.C.B. LAYOUT

# E-SWITCH®

REV. A		12540		RELEASED FOR PRODUCTION		7/1/02		CJB	
REV. ECN No.		DESCRIPTION		DATE		CHKD		SCALE	
THE INFORMATION CONTAINED IN THIS DOCUMENT IS PROPRIETARY TO E-SWITCH AND IS NOT TO BE COPIED OR TRANSFERRED		RECOMMENDED P.C.B. LAYOUT		TITLE		DATE		DR	
				KAJ03 SG GT (GOLD) LOW PROFILE W/O TAPE		7/1/02		CJB	
				SCALE		DATE		DWG	
				2:1		7/1/02		W825223	
								REV	
								A	