5-5223963-1 V ACTIVE



Z-PACK 2mm HM

TE Internal #: 5-5223963-1

Rectangular Power Connectors, Connector Assembly, Plug, Boardto-Board, 3 Position, 3 mm [.118 in] Centerline, Printed Circuit

Board, Z-PACK 2mm HM

View on TE.com >



Connectors > Power Connectors > Rectangular Power > Rectangular Power Connectors



Rectangular Power Connector Type: Connector Assembly

Connector & Housing Type: Plug Connector System: Board-to-Board

Number of Positions: 3

Centerline (Pitch): 3 mm [.118 in]

Features

Product Type Features

Header Type	Fully Shrouded
Rectangular Power Connector Type	Connector Assembly
Connector & Housing Type	Plug
Connector System	Board-to-Board
Sealable	No
Connector & Contact Terminates To	Printed Circuit Board
Configuration Features	
Number of Positions	3
PCB Mount Orientation	Right Angle
Number of Power Positions	3
Number of Signal Positions	0
Number of Rows	1
Electrical Characteristics	

Electrical Characteristics

Operating Voltage	250 VDC

Contact Features

Contact Mating Area Plating Material	Gold, Gold Flash over Palladium Nickel
Contact Underplating Material	Nickel
Contact Base Material	Copper Alloy



Contact Current Rating (Max)	16 A
Contact Retention Within Housing	With
Contact Type	Blade
PCB Contact Termination Area Plating Material	Gold
Contact Mating Area Plating Material Thickness	1.27 μm[50 μin]
Termination Features	
Termination Method to Printed Circuit Board	Through Hole - Press-Fit
Mechanical Attachment	
Connector Mounting Type	Board Mount
Housing Features	
Centerline (Pitch)	3 mm[.118 in]
Housing Color	Gray
Housing Material	Thermoplastic
Housing Material Usage Conditions	Thermoplastic
	Thermoplastic -55 – 125 °C[-67 – 257 °F]
Usage Conditions	
Usage Conditions Operating Temperature Range	
Usage Conditions Operating Temperature Range Operation/Application	-55 – 125 °C[-67 – 257 °F]
Usage Conditions Operating Temperature Range Operation/Application Circuit Application	-55 – 125 °C[-67 – 257 °F]
Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards	-55 – 125 °C[-67 – 257 °F] Power
Usage Conditions Operating Temperature Range Operation/Application Circuit Application Industry Standards UL Flammability Rating	-55 – 125 °C[-67 – 257 °F] Power UL 94V-0

Product Compliance

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant
EU ELV Directive 2000/53/EC	Compliant
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC



Halogen Content	Not Low Halogen - contains Br or Cl > 900
	ppm.

Solder Process Capability

Not applicable for solder process capability

Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

Compatible Parts



Also in the Series | Z-PACK 2mm HM



Backplane Coding Keys(60)



Backplane Connector Housings(4)




Backplane Guide Hardware(37)



Backplane Power Connectors(6)



Board-to-Board Connector Contacts(2)



Hard Metric Backplane Connectors




High Speed Backplane Connectors(1)



Insertion & Extraction Tools(2)





PCB Connector Covers(4)



PCB Connector Shrouds(39)



PCB Ferrules & Shields(19)



Rectangular Power Connectors(87)

Customers Also Bought



TE Part #6609013-2 6EH9=F7288 S0



TE Part #2007394-5 SFP+assy 2x4 Spring Fingers 4



TE Part #1489951-1
XFP CAGE ASSEMBLY



TE Part #644753-4
04P MTA156 HDR ASSY RN STR F/L



TE Part #5223955-2
TE UPM Ver Receptacle 3P STD Power



TE Part #1761014-3 SFP 1X2 CAGE ASSY, PRESS FIT



TE Part #1825263-1 MSS225004=DPDT SL SW VERT AG



TE Part #6-103908-5 16 MTE HDR SRST LATCH W/HLDWN



Documents

Product Drawings

UPM R/A Header 3P HC Power Conn, MLM

English

CAD Files

3D PDF

3D

Customer View Model

ENG_CVM_CVM_5-5223963-1_C1.2d_dxf.zip



English

Customer View Model

ENG_CVM_CVM_5-5223963-1_C1.3d_igs.zip

English

Customer View Model

ENG_CVM_CVM_5-5223963-1_C1.3d_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use.

Datasheets & Catalog Pages

POWER_CONNECTORS_CATALOG_SEC01_BOARD_TO_BOARD

English

Solutions for AdvancedTCA, AdvancedTCA 300, MicroTCA, and AdvancedMC Standards Datasheet 3-1773445-8

English

2_PIECE_POWER_CONNECTORS_qrg_4-1773458-1

English

Product Specifications

Engineering Report

English

Product Environmental Compliance

TE Material Declaration

English