

Cable gland - G-INS-NPT3/4-M68L-NNES-S - 1411184

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Cable gland, Cable gland material: Brass, nickel-plated, External cable diameter 13 mm ... 18 mm, Shielding: No, Connecting thread: 3/4 inch NPT, Color: silver



Key Commercial Data

Packing unit	1 pc
Minimum order quantity	5 pc
Weight per Piece (excluding packing)	72.0 g
Custom tariff number	74199990
Country of origin	Turkey

Technical data

Dimensions

Length	48 mm
Wrench size, union nut	30 mm
Wrench size, support	30 mm
Hexagon angular dimension GRP	33 mm
Length of the connecting thread	13 mm
External cable diameter	13 mm ... 18 mm

Ambient conditions

Degree of protection	IP68
	4X
Ambient temperature (operation)	-20 °C ... 100 °C (static)

General

Cable gland material	Brass, nickel-plated
Seal material	Neoprene
Cable seal material	Neoprene

Cable gland - G-INS-NPT3/4-M68L-NNES-S - 1411184

Technical data

General

O-ring material	NBR
Shielded	No
Thread type on connection side	3/4 inch NPT
Torque	15 Nm ... 20 Nm (Union nut)
Color	silver

Standards and Regulations

Connection in acc. with standard	UL
----------------------------------	----

Classifications

eCl@ss

eCl@ss 5.1	27081002
eCl@ss 6.0	27081002
eCl@ss 8.0	27149109

ETIM

ETIM 4.0	EC000441
ETIM 5.0	EC000441

Approvals

Approvals

Approvals

UL Listed / cUL Listed / cULus Listed

Ex Approvals

Approvals submitted

Approval details

UL Listed

Cable gland - G-INS-NPT3/4-M68L-NNES-S - 1411184


Approvals

cUL Listed 

cULus Listed 

Drawings

Dimensional drawing



Dimensional drawing