


Data sheet

SmartConnect Patchpanel 16 ports MC module

Illustrations



Dimensional drawing



See enlarged drawings at the end of document

Product specification

- empty module holder for receiving data, KOAX and fiber optic modules
- mounting type: module
- mounting on standard rail (TH35) or on support frame or mounting plate screwable
- consisting of 1 module holder made of bent sheet metal and 2 milled plastic brackets universally applicable for all variants
- mounting the plastic brackets on standard rail and perforated metal plate
- functional equipotential bonding acc. to DIN EN 50310 (VDE0800-2-310) with 2 screw fastenings via grounding screw M6x10 with nut and lock washer possible
- 1 labeling strip on module holder
- variants: 12, 16, 24 ports

SmartConnect Patchpanel 16 ports MC module

P/N

130927-1600-E

EAN 4251394635446

2023/04/18

Version: B

Technical Data

General Data

Fields of application	structured building cabling Distributed building services
Mechanical measurement according to MICE	M1
Ingress measurement according to MICE	I1
Climatic measurement according to MICE	C1
Electromagnetic measurement according to MICE	E3
Design	patch panel
Mounting style	standard rail TH35, perforated metal plate
Color	gray
Dimensions	
Dimension (L x W x H)	338 mm x 53.5 mm x 53.5 mm
Dimension (L x W x H)	13.307 in. x 2.106 in. x 2.106 in.
Weight	287 g
Weight	0.6327 lb
Modularity	yes
Labeling option	labeling strip on module holder

Connections/interfaces

Number of ports interface 1	16
Number of equipped ports interface 1	0
Cable access/outlet	45° upwards
Ground connection	grounding screw M6x10 with nut and lock washer

Mechanical data

Cut-out	module
---------	--------

Materials and material properties

Material - Housing	aluminium-zinc sheet
Material - Mounting	PVC
Halogen free	yes
RoHS	compliant

SmartConnect Patchpanel 16 ports MC module

P/N

130927-1600-E**EAN 4251394635446**

2023/04/18

Version: B

Technical Data**Classifications**

ETIM 7.0	EC002006
ETIM 8.0	EC002006
ETIM 9.0	EC002006

Packing details

Type of packaging	1 pc(s) / plastic bag
Packaging unit - Weight (gram)	300 g
Packaging unit - Weight (pound)	0.66 lb
Packaging dimension	54 mm x 340 mm x 65 mm
Packaging dimension	2.12 in. x 13.39 in. x 2.56 in.

SmartConnect Patchpanel 16 ports MC module

P/N

130927-1600-E

EAN 4251394635446

2023/04/18

Version: B

Accessories

P/N	Designation
1308450233-E	Patch cord Cat.6 _A AWG 26 0.2 m gray
1308450333-E	Patch cord Cat.6 _A AWG 26 0.3 m gray
1308450533-E	Patch cord Cat.6 _A AWG 26 0.5 m gray
1308451033-E	Patch cord Cat.6 _A AWG 26 1.0 m gray
13084U0300-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 0.3 m black
13084U0333-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 0.3 m gray
13084U0388-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 0.3 m white
13084U0500-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 0.5 m black
13084U0533-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 0.5 m gray
13084U0588-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 0.5 m white
13084U1000-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 1.0 m black
13084U1033-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 1.0 m gray
13084U1088-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 1.0 m white
13084V0300-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 0.3 m black
13084V0333-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 0.3 m gray
13084V0388-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 0.3 m white
13084V0500-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 0.5 m black
13084V0533-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 0.5 m gray
13084V0588-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 0.5 m white
13084V1000-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 1.0 m black
13084V1033-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 1.0 m gray
13084V1088-E	Patch cord Cat.6 Ultraflex500 VoIP AWG 26 1.0 m white

SmartConnect Patchpanel 16 ports MC module

P/N

130927-1600-E

EAN 4251394635446

2023/04/18

Version: B

Accessories

130898-00-I	BLIND module light gray
130898-00-RW-I	BLIND module pure white
130898-01-I	COAX modul F jack / F jack
130898-02-I	COAX modul IEC jack / F jack
130898-03-I	COAX modul IEC plug / F jack
130908-I-B1	UAE modul Cat.5e white
130909-I	UAE modul Cat.6 jack T568A white
130910-I	E-DAT modul Cat.6 _A 8(8) jack, T568A
130910-I-B1	E-DAT modul Cat.6 _A 8(8) jack, T568B
130910-Z	E-DAT modul Cat.6 _A 8(8) jack, T568A (12 pcs)
1309A0-I	E-DAT modul coupler 8(8) 180° class E _A
130A11-29-I	UAE modul 8(8) Cat.6 _A black
130A11-I	UAE modul 8(8) Cat.6 _A white
130B11-25-E	25Gmodul
130B11-25-Z	25Gmodul (12 pcs)
130B11-E	C6 _A modul 180° jack
130B11-Z	C6 _A modul 180° jack (12 pcs)
15091001-I	OpDAT modul ST OS2
15091071-I	OpDAT modul LC-Duplex OS2
15091072-I	OpDAT modul LC-Duplex OM3
15091075-I	OpDAT modul LC-Duplex OM4
15091076-I	OpDAT modul LC-Duplex APC OS2
1509107B-I	OpDAT modul LC-Duplex OM2
1509107M-I	OpDAT modul LC-Duplex OM5

Illustrations

Dimensional drawing

