



Recommended PCB Layout
(Top View)

Part Number	Contact Area Plating Finish
K31X-A15S-N	Gold Flash (Standard)
K31X-A15S-N15	15u" Gold (15 Option)
K31X-A15S-N30	30u" Gold (30 Option)

Material and Finish

Insulator: PBT Thermoplastic with Glass-fiber Reinforcement, UL 94V-0 Rated, Color: Black

Shell: Steel, Nickel Plated

Contact Material:
Socket - Phosphor Bronze

Contact Plating Options:

Standard: Gold Flash on Mating End, Tin on Termination End, Nickel Underplate on Entire Contact

15 Option: 15u" Gold on Mating End, Tin on Termination End, Nickel Underplate on Entire Contact

30 Option: 30u" Gold on Mating End, Tin on Termination End, Nickel Underplate on Entire Contact

Electrical Specifications

Rated Current: 2A

Rated Voltage: 30V RMS

Insulation Resistance:
1000 Megohms Min. at 500V DC

Contact Resistance:
13 milliohms Max.

Dielectric Withstanding Voltage:
1000V for 1 Minute

Mechanical Specifications

Operating Temperature:
-55°C to +105°C



Tolerances
X.X ± 0.25
X.XX ± 0.15
Unless Stated Otherwise

REV.	DATE	DESCRIPTION	REV. BY	CHK. BY	DRAWN BY	DATE
A1	10/05/05	New Drawing	R. Aguirre	H. MA	R. Aguirre	10/05/05
A2	03/06/08	ECO #07-051	S. Vien	H. MA		
A3	06/04/08	Remove Dim.	S. Vien	H. MA		
A4	10/01/12	ECO #12-052	S. Vien	P. DalCanto		
A5	05/06/13	ECO #13-027	D. Gih	P. DalCanto		UNITS
A6	12/31/17	ECO #17-041	G. Serrato	C. Furumasu		mm

K31X-A15S-N

D-Sub, 15 Pin Female, RoHS Compliant

Ultra Compact Footprint

