12 INCHES LENGTH



Connector A 132119 SMA Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-174 Continuity/Hi-Pot Connector B 034-5019 HD-BNC Jack Straight Bulkhead - Rear Mount Brass Nickel + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

] [Connector A			Cable			Connector B		
	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting:	132119 SMA BHD JK RG174 RG188 RG316 500 SMA Jack Straight Solder Standard 50 Ohm Bulkhead - Rear Mount Brass Gold None Beryllium Copper Gold 12.4 GHz SMA Jack Straight BHD		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-174 RG-174 - PE 0.1 PE Braid 0.1 50 Ohm None Continuity Hi-Pot 12 Inches	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	034-5019 HD-BNC BHD JK R HD-BNC Jack Straight Solder Standard 50 Ohm Bulkhead - Rear Mo Brass Nickel None Beryllium Copper Gold 6 GHz HD-BNC Jack Straig 0°	unt	
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT DO NOT CONV CUSTOM CABLE			THIS DRAWING MAY CONTAIN PROPRIETARY INFORMATION FOR ANY PURPOSE DETRIMEN INC. IT MAY NOT BE REPRODU IN ANY FORM WITHOUT THE V CUSTOM CABLE INC. ACCEPT ESTABLISHES AND AGREEMEN	AND MUST NOT BE U ITAL TO CUSTOM CA JCED OR TRANSCRIB WRITTEN CONSENT O ANCE OF THIS DRAW	BLE ED FF ING Part No:	SMA-ST-JK/HDBNC-ST-JK G174 12I		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	