

3994.8 AQI 10/10/18 YE



External insulated cross-connector, No. of poles: 10, Mounting type: Plug in, Width: 98.9 mm, Rated current: 57 A; Colour: Yellow

RAL: 1026

Business data

| | |
|--|------------------------------------|
| Article number | 3994.8 |
| Article name | AQI 10/10/18 YE |
| GTIN (EAN) | 4044211130428 |
| Packaging unit | 10 |
| Quantity unit | PC |
| Weight per piece (not including packaging) | 15.2 g |
| Weight per piece (including packaging) | 15.4 g |
| Unit of weight | G |
| Customs number | 85389099 |
| Country of origin | DE |
| Product description | External insulated cross-connector |
| Colour | Yellow |

Technical data

Dimensions

| | |
|-------|---------|
| Width | 98.9 mm |
|-------|---------|

| | |
|------------|-------|
| Pitch size | 10 mm |
|------------|-------|

Ratings

| | |
|---------------|------|
| Rated current | 57 A |
|---------------|------|

| | |
|----------------------|---|
| Contamination degree | 3 |
|----------------------|---|

Connection data

| | |
|--------------|----|
| No. of poles | 10 |
|--------------|----|

Materials

| | |
|----------|--------|
| Material | Copper |
|----------|--------|

| | |
|---------|------------|
| Surface | Tin-plated |
|---------|------------|

| | |
|--------------------|---------------|
| Insulation housing | Polyamide 6.6 |
|--------------------|---------------|

| | |
|--------------------------|-----|
| Flammability class UL 94 | V-0 |
|--------------------------|-----|

| | |
|---------------------------|--------|
| Working temperature, min. | -40 °C |
|---------------------------|--------|

| | |
|---------------------------|--------|
| Working temperature, max. | 120 °C |
|---------------------------|--------|

Further technical data

| | |
|---------------|---------|
| Mounting type | Plug in |
|---------------|---------|

| | |
|----------------------|---|
| Insulation available | ✓ |
|----------------------|---|

| | |
|-------------------------------|---|
| Touch protection is available | ✓ |
|-------------------------------|---|

| | |
|-----------------------------|----|
| Number of bridged terminals | 10 |
|-----------------------------|----|

Environmental Product Compliance

| | |
|---------------|-----|
| REACH Conform | yes |
|---------------|-----|

| | |
|----------------------|------------|
| REACH Reference date | 2023-01-17 |
|----------------------|------------|

| | |
|--------------------------------|----|
| REACH Candidate Substance Note | No |
|--------------------------------|----|

| | |
|--------------|-----|
| RoHS Conform | yes |
|--------------|-----|

Media

Accessories

##INVERSE##CONTA-CONNECT



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 10 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-----------------------------------|---------------|----------------|
| <u>1108.2</u> | SIK 10/Z/LED(RD)/12V DC/24V AC BG | 4044211017118 | 25 ST |



Fused terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 10 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|------------------|---------------|----------------|
| <u>17365.4</u> | SIK 10/Z PA-G BK | 4044211178390 | 25 ST |



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 10 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--|---------------|----------------|
| <u>1110.2</u> | SIK 10/Z/LED(RD)/40-60V DC/80-120V AC BG | 4044211017439 | 25 ST |



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 10 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|-------------------------------------|---------------|----------------|
| <u>1111.2</u> | SIK 10/Z/LED(RD)/115V DC/230V AC BG | 4044211017446 | 25 ST |



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 10 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---|---------------|----------------|
| <u>1109.2</u> | SIK 10/Z/LED(RD)/20-30V DC/40-60V AC BG | 4044211017323 | 25 ST |



Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 10 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|----------------|---------------|----------------|
| <u>17043.2</u> | SIK 10/Z/ST BG | 4044211155810 | 25 ST |

##INVERSE##CONTA-CONNECT



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 10 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------------------------|---------------|----------------|
| <u>1112.2</u> | SIK 10/Z/2 LED's(RD)/24V DC BG | 4044211017477 | 25 ST |



Fuse-disconnect terminal, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 10 mm, Colour: Beige

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|--------------|---------------|----------------|
| <u>1102.2</u> | SIK 10/Z BG | 4044211016395 | 25 ST |



Fused terminal with disconnect plug, Screw connection, Mounting type:Mounting rail TS 35/7.5 and TS 32, Rated cross-section: 10 mm², Width: 10 mm, Colour: Black

| Article number | Article name | GTIN (EAN) | Packaging unit |
|----------------|---------------------|---------------|----------------|
| <u>17041.4</u> | SIK 10/Z/ST PA-G BK | 4044211155780 | 25 ST |