36 INCHES LENGTH



Connector A 132443 SMA Plug Straight Brass Gold + Heatshrink 50 Ohm LMR-195 Continuity/Hi-Pot Connector B 172384 N-Type Jack Straight Bulkhead - Rear Mount Brass White Bronze + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

| | Connector A | | | Cable | | | Connector B | | |
|---|-----------------------------------|------------------|---|--|---------------------|-------------------|---|-----------------------------------|--|
| | Part #: | 132443 | | Part #: | LMR-195 | Part #: | 172384 | | |
| | Description: | SMA PLUG LMR | 195 Optimized 50O | Description: | LMR-195 - FEP 0.195 | Description: | N-Type BHD JK Opt | timized LMR195 50O | |
| | Type: | SMA | | Dielectric: | FEP | Type: | N-Type | | |
| | Gender: | Plug | | Shielding: | Braid | Gender: | Jack | | |
| | Body Type: | Straight | | Diameter: | 0.195 | Body Type: | Straight | | |
| | Contact Type: | Solder | | Impedance: | 50 Ohm | Contact Type: | Crimp | | |
| | Polarity: | Standard | | Sheathing: | None | Polarity: | Standard | | |
| | Impedance: | 50 Ohm | | Testing: | Continuity Hi-Pot | Impedance: | 50 Ohm | | |
| | Mounting: | Cable | | Length: | 36 Inches | Mounting: | Bulkhead - Rear Mo | ount | |
| | Body Material: | Brass | | , J. | | Body Material: | Brass | | |
| | Body Finish: | Gold | | | | Body Finish: | White Bronze | | |
| | IP Rating: | None | | | | IP Rating: | None | | |
| | Contact Material: | Brass | | | | Contact Material: | Phosphor Bronze | | |
| | Contact Finish: | Gold | | | | Contact Finish: | Gold | | |
| | Max. Freq.: | 6 GHz | | | | Max. Freq.: | 6 GHz | | |
| | Booting: | SMA Plug Straigh | it | | | Booting: | N-Type Jack Straigh | nt BHD | |
| | | | | | | Clocking: | 0° | | |
| THIS DRAWING MAY CONTAIN | | | | Title: | | | UNLESS SPECIFIED | | |
| mphenol This DRAWING MAY CONTA PROPRIETARY INFORMATIO FOR ANY PURPOSE DETRIMING. STOM CABLE IN ANY FORMULT THIS | | | ITAL TO CUSTOM CABLE JCED OR TRANSCRIBED | | K LMR19 361 | | TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% | | |
| | | | | FORM WITHOUT THE WRITTEN CONSENT OF I CABLE INC. ACCEPTANCE OF THIS DRAWING | | Part No: | | ASSEMBLY: CENTER LABEL IF LENC | |
| CONTROLLED DOC | CONTROLLED DOCUMENT - DO NOT COPY | | | ESTABLISHES AND AGREEMENT OF THE FOREGOING. | | Q-3E023000D036I | | IS LESS THAN 12 INCH | |



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/2/2023

Part Number: Q-3E023000D036I

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-PL/N-ST-JK LMR19 36I

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

Janice Frank