

Product data sheet

Specifications



Sealed pressure balance valves IP68 ØM12 F16 liters/hour when 0,07 bar

NSYCAG12LPH1

Main

Range	ClimaSys
Product	ClimaSys CA
Range compatibility	Thalassa (Thalassa PLS) Thalassa (Thalassa PLM) Thalassa (Thalassa TBS) Thalassa (Thalassa TBP)
Product or component type	Pressure release valve
Accessory / separate part category	Thermal management accessory
Environmental characteristic	Water resistant
Fixing mode	Screwed
Device composition	1 valve
Quantity per set	Set of 10

Complementary

Material	Membrane: acrylic co-polymer PA6
Diameter	11.5 mm
Height	17.1 mm
Width	18.3 mm
Flame retardance	V2
Operating temperature	-40...150 °C
Permeability	16 l/h
Pressure difference	< 1 bar

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	1.78 cm
Package 1 Width	1.78 cm
Package 1 Length	1.78 cm
Package 1 Weight	4 g

Unit Type of Package 2	BB1
Number of Units in Package 2	10
Package 2 Height	2.5 cm
Package 2 Width	8 cm
Package 2 Length	14 cm
Package 2 Weight	40 g
Unit Type of Package 3	PAL
Number of Units in Package 3	400
Package 3 Height	20 cm
Package 3 Width	30 cm
Package 3 Length	40 cm
Package 3 Weight	1.6 kg

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Toxic heavy metal free	Yes
Mercury free	Yes
China RoHS Regulation	China RoHS declaration Pro-active China RoHS declaration (out of China RoHS legal scope)
RoHS exemption information	Yes
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------

Recommended replacement(s)