

NSYS3D8830T

Spacial S3D tspt door w/o
mount.plate.H800xW800xD300.IP66 IK08
RAL7035.



Main

Range	Spacial
Product name	Spacial S3D
Application	Multi-purpose
Category	Compact enclosure
Enclosure nominal height	31.50 in (800 mm)
Enclosure nominal width	31.50 in (800 mm)
Enclosure nominal depth	11.81 in (300 mm)
Door type	Glass
Mounting plate description	Without mounting plate
Type of gland plate	Standard
Installation accessory type	Wall-mounting
Device composition	1 body 2 cable gland plate 1 door 1 lock

Complementary

Body type	Single piece body Gutter-shaped front rail double sheet thickness
Number of doors	Front face 1
Door opening side	Reversible 120 °)
Lock type	3 points lock, 3 mm double-bar
Accessibility for operation	Front
Removable parts	Door by hinges Cable gland plate by screws
Material	Body steel Door steel and security glass
Surface finish	Epoxy-polyester powder
Color	Gray RAL 7035)
Standards	IEC 62208
Product Certifications	LR BV UL CUL GL DNV
Net Weight	68.34 lb(US) (31 kg)

Environment

Electromagnetic compatibility	Electromagnetic field immunity test
NEMA Degree of Protection	NEMA 4X/13
IK degree of protection	IK08 IEC 62262
IP degree of protection	IP66 IEC 60529

Ordering and shipping details

Category	80034-ENCLOSURE SYSTEMS WALL MOUNT METAL
Discount Schedule	ES1
GTIN	3606480158834
Nbr. of units in pkg.	1
Package weight(Lbs)	68.34 lb(US) (31.0 kg)
Returnability	No
Country of origin	FR

Packing Units

Unit Type of Package 1	PCE
Package 1 Height	32.44 in (82.4 cm)
Package 1 width	32.52 in (82.6 cm)
Package 1 Length	13.94 in (35.4 cm)

Offer Sustainability

Sustainable offer status	Green Premium product
REACH Regulation	REACH Declaration
REACH free of SVHC	Yes
EU RoHS Directive	Pro-active compliance (Product out of EU RoHS legal scope) EU RoHS Declaration
Mercury free	Yes
RoHS exemption information	Yes
China RoHS Regulation	China RoHS Declaration
Environmental Disclosure	Product Environmental Profile

Contractual warranty

Warranty	18 months
----------	-----------