

## High Sensitivity Omni-Polar Hall Effect Switch

### TO-92S



#### Pin Definition:

1. V<sub>CC</sub>
2. GND
3. Output

### SOT-23



#### Pin Definition:

1. V<sub>CC</sub>
2. Output
3. GND

## Description

TSH253 Hall-effect sensor is a temperature stable, stress-resistant switch. Superior high-temperature performance is made possible through a dynamic offset cancellation that utilizes chopper-stabilization. This method reduces the offset voltage normally caused by device over molding, temperature dependencies, and thermal stress. TSH253 includes the following on a single silicon chip: voltage regulator, Hall voltage generator, small-signal amplifier, chopper stabilization, Schmitt trigger, open-drain output. Advanced CMOS wafer fabrication processing is used to take advantage of low-voltage requirements, component matching, very low input-offset errors, and small component geometries.

## Features

- CMOS Hall IC Technology
- Solid-State Reliability much better than reed switch
- Omni polar output switches with absolute value of North or South pole from magnet
- Operation down to 1.8 V and Max at 6V.
- High Sensitivity for reed switch replacement
- ESD HBM ±4KV Min

## Ordering Information

| Part No.     | Package | Packing          |
|--------------|---------|------------------|
| TSH253CT B0G | TO-92S  | 1Kpcs / Bulk Bag |
| TSH253CX RFG | SOT-23  | 3Kpcs / 7" Reel  |

**Note:** "G" denote for Halogen Free Product

## Application

- Solid state switch, Revolution counter
- Lid close sensor for power supply devices
- Magnet proximity sensor for reed switch replacement in high duty cycle applications.
- Safety Key on sporting equipment
- Speed sensor, Position Sensor, Rotation Sensor


## Absolute Maximum Rating (T<sub>a</sub> = 25°C unless otherwise noted)

| Characteristics                          | Limit               | Value       | Unit  |
|--|---------------------|-------------|-------|
| Supply voltage                           | V <sub>CC</sub>     | 6           | V     |
| Output Voltage                           | V <sub>OUT</sub>    | 6           | V     |
| Reverse voltage                          | V <sub>CC/OUT</sub> | -0.3        | V     |
| Magnetic flux density                    |                     | Unlimited   | Gauss |
| Output current                           | I <sub>OUT</sub>    | 1           | mA    |
| Operating Temperature Range              | T <sub>OPR</sub>    | -40 to +85  | °C    |
| Storage temperature range                | T <sub>STG</sub>    | -55 to +150 | °C    |
| Maximum Junction Temp                    | T <sub>J</sub>      | 150         | °C    |
| Thermal Resistance - Junction to Ambient | TO-92S              | 206         | °C/W  |
|  | SOT-23              | 543         |       |
| Thermal Resistance - Junction to Case    | TO-92S              | 148         | °C/W  |
|  | SOT-23              | 410         |       |
| Package Power Dissipation                | TO-92S              | 606         | mW    |
|  | SOT-23              | 230         |       |

**Note:** Exceeding the absolute maximum ratings may cause permanent damage. Exposure to absolute maximum-rated conditions for extended periods may affect device reliability.


## High Sensitivity Omni-Polar Hall Effect Switch

### Block Diagram



**Note:** Static sensitive device; please observe ESD precautions. Reverse VDD protection is not included. For reverse voltage protection, a 100Ω resistor in series with VDD is recommended.

### Typical Application Circuit



### Electrical Specifications (DC Operating Parameters : $T_A=+25^{\circ}\text{C}$ , $V_{CC}=5\text{V}$ )

| Parameters               | Test Conditions                                       | Min | Typ | Max  | Units |
|--------------------------|---|-----|-----|------|-------|
| Supply Voltage           | Operating   | 1.8 | --  | 6    | V     |
| Supply Current           | Average   | --  | 2.6 | 6.0  | mA    |
| Output Low Voltage       | $I_{OUT}=0.5\text{mA}$                                | --  | --  | 200  | mV    |
| Output Leakage Current   | $I_{OFF} \quad B < B_{RP}, \quad V_{OUT} = 3\text{V}$ | --  | --  | 10   | uA    |
| Output Rise Time         | $R_L=10\text{k}\Omega, \quad C_L=20\text{pF}$         | --  | --  | 0.45 | uS    |
| Output Fall Time         | $R_L=10\text{k}\Omega; \quad C_L=20\text{pF}$         | --  | --  | 0.45 | uS    |
| Electro-Static Discharge | HBM   | 4   | --  | --   | KV    |

**Magnetic Specifications (TSH253CT)**

| Parameter       | Symbol           | Test Conditions  | Min. | Typ. | Max. | Units |
|-----------------|------------------|--|------|------|------|-------|
| Operating Point | B <sub>OPS</sub> | S pole to branded side, B > B <sub>OP</sub> , Vout On  |      | 30   | 60   | Gauss |
|                 | B <sub>OPN</sub> | N pole to branded side, B > B <sub>OP</sub> , Vout On  | -60  | -30  |      | Gauss |
| Release Point   | B <sub>RPS</sub> | S pole to branded side, B < B <sub>RP</sub> , Vout Off | 5    | 25   |      | Gauss |
|                 | B <sub>RPN</sub> | N pole to branded side, B < B <sub>RP</sub> , Vout Off |      | -25  | -5   | Gauss |
| Hysteresis      | B <sub>HYS</sub> | BOP <sub>x</sub> - BRP <sub>x</sub>                    |      | 5    |      | Gauss |

Note: 1G (Gauss) = 0.1mT (millitesta)

**Magnetic Specifications (TSH253CX)**


| Parameter       | Symbol           | Test Conditions  | Min. | Typ. | Max. | Units |
|-----------------|------------------|--|------|------|------|-------|
| Operating Point | B <sub>OPS</sub> | N pole to branded side, B > B <sub>OP</sub> , Vout On  | --   | 30   | 60   | Gauss |
|                 | B <sub>OPN</sub> | S pole to branded side, B > B <sub>OP</sub> , Vout On  | -60  | -30  | --   | Gauss |
| Release Point   | B <sub>RPS</sub> | N pole to branded side, B < B <sub>RP</sub> , Vout Off | 5    | 25   | --   | Gauss |
|                 | B <sub>RPN</sub> | S pole to branded side, B < B <sub>RP</sub> , Vout Off | --   | -25  | -5   | Gauss |
| Hysteresis      | B <sub>HYS</sub> | BOP <sub>x</sub> - BRP <sub>x</sub>                    | --   | 5    | --   | Gauss |

Note: 1G (Gauss) = 0.1mT (millitesta)


**Output Behavior versus Magnetic Pole**

DC Operating Parameters: T<sub>A</sub> = -40 to 125°C, V<sub>CC</sub> = 1.8V ~ 6V


| Parameter                   | Test condition      | OUT                   |
|-----------------------------|---------------------|-----------------------|
| South pole                  | B < Bop[(-60)~(-5)] | Low                   |
| Null or weak magnetic field | B=0 or B < BRP      | Open(Pull-up Voltage) |
| North pole                  | B > Bop(60~5)       | Low                   |




**Characteristic Performance**




**Figure 1. Supply Voltage vs. Flux Density**




**Figure 2. Temperature vs. Flux Density**




**Figure 3. Supply Current vs. Temperature**



**Figure 4. Supply Current vs. Supply Voltage**




**Figure 5. Output Saturation Voltage vs. Supply Voltage**




**Figure 6. Output Saturation Voltage vs. Temperature**

**Characteristic Performance**



**Figure 7. Output Leakage Current vs. Supply Voltage**




**Figure 8. Power Dissipation vs. Temperature**

**TO-92S Mechanical Drawing**




Unit: Millimeters

**Marking Diagram**




**253** = Device Code  
**Y** = Year Code (3=2013, 4=2014....)  
**WW** = Week Code (01~52)

**SOT-23 Mechanical Drawing**



Unit: Millimeters

**Marking Diagram**



**253** = Device Code  
**WW** = Week Code Table

|      |    |    |    |    |    |    |    |    |    |    |    |    |    |
|------|----|----|----|----|----|----|----|----|----|----|----|----|----|
| week | 1  | 2  | 3  | 4  | 5  | 6  | 7  | 8  | 9  | 10 | 11 | 12 | 13 |
| code | OA | OB | OC | OD | OE | OF | OG | OH | OI | OJ | OK | OL | OM |
| week | 14 | 15 | 16 | 17 | 18 | 19 | 20 | 21 | 22 | 23 | 24 | 25 | 26 |
| code | ON | OO | OP | OQ | OR | OS | OT | OU | OV | OW | OX | OY | OZ |
| week | 27 | 28 | 29 | 30 | 31 | 32 | 33 | 34 | 35 | 36 | 37 | 38 | 39 |
| code | PA | PB | PC | PD | PE | PF | PG | PH | PI | PJ | PK | PL | PM |
| week | 40 | 41 | 42 | 43 | 44 | 45 | 46 | 47 | 48 | 49 | 50 | 51 | 52 |
| code | PN | PO | PP | PQ | PR | PS | PT | PU | PV | PW | PX | PY | PZ |

## Notice

Specifications of the products displayed herein are subject to change without notice. TSC or anyone on its behalf, assumes no responsibility or liability for any errors or inaccuracies.

Information contained herein is intended to provide a product description only. No license, express or implied, to any intellectual property rights is granted by this document. Except as provided in TSC's terms and conditions of sale for such products, TSC assumes no liability whatsoever, and disclaims any express or implied warranty, relating to sale and/or use of TSC products including liability or warranties relating to fitness for a particular purpose, merchantability, or infringement of any patent, copyright, or other intellectual property right.

The products shown herein are not designed for use in medical, life-saving, or life-sustaining applications. Customers using or selling these products for use in such applications do so at their own risk and agree to fully indemnify TSC for any damages resulting from such improper use or sale.