



NOTES:

MECHANICAL

RJ45
PLUG: CLEAR POLYCARBONATE
BOOT: BLACK PVC

CABLE: 26 AWG SHIELDED ETHERNET CABLE CAT-5E STRANDED TEAL TPE

WRAP LABEL: MARKED WITH P/N, DATE CODE, VOLTAGE & AMPERAGE

ELECTRICAL

ACCORDING TO CAT5e
VOLTAGE RATING: 30V AC/DC
AMPERAGE: 1.5A

ADDED PART NO. TABLE EC NO: IPG2015-2010 DRWN: GGUSTAFS 2015/05/27 CHKD: BARDEN 2015/07/23 APPR: BWOODMAN 2015/04/03	DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCH ONLY		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION		
		$\nabla=0$ $\nabla C=0$	mm	INCH	DRAWN BY	DATE	TITLE RJ45 TO RJ45 CORDSET RJ45 ST / RJ45 ST #26/4 TEAL TPE				
			4 PLACES	±---	±---	GGUSTAFS					
			3 PLACES	±---	±.005	CHECKED BY	DATE				
2 PLACES	±.13	±.010	BARDEN	2015/05/29	MOLEX INCORPORATED DOCUMENT NO. SD-120108-079 SHEET NO. 1 OF 2						
1 PLACE	±.25	±.020	APPROVED BY	DATE							
ANGULAR ±.5°			DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS		MATERIAL NO. SEE TABLE		THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION				

MATERAIL NO.	ENGINEERING NO.
1201080400	E66A06005M010
1201080314	E66A06005M020
1201080401	E66A06005M050
1201080402	E66A06005M100
1201080315	E66A06005M150
1201080403	E66A06005M200
1201080316	E66A06005M300
1201080320	E66A06005M500
1201080319	E66A06005M900

E66A06005M010

cable type
 TPE Teal

cable length
 M010----1 Meter
 M100----10 Meter

ADDED PART NO. TABLE EC NO: IPG2015-2010 DRWN: GGUSTAFS 2015/05/27 CHKD: BARDEN 2015/07/23 APPR: BWOODMAN 2015/04/03	DESCRIPTION REV	QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)		DIMENSION STYLE INCH ONLY		SCALE NTS	DESIGN UNITS INCH	THIRD ANGLE PROJECTION																											
		$\nabla=0$ $\nabla C=0$	<table border="1"> <tr> <th></th> <th>mm</th> <th>INCH</th> </tr> <tr> <td>4 PLACES</td> <td>±---</td> <td>±---</td> </tr> <tr> <td>3 PLACES</td> <td>±---</td> <td>±.005</td> </tr> <tr> <td>2 PLACES</td> <td>±.13</td> <td>±.010</td> </tr> <tr> <td>1 PLACE</td> <td>±.25</td> <td>±.020</td> </tr> </table>		mm	INCH	4 PLACES	±---	±---	3 PLACES	±---	±.005	2 PLACES	±.13	±.010	1 PLACE	±.25	±.020	ANGULAR ±.5°	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS	<table border="1"> <tr> <td>DRAWN BY</td> <td>DATE</td> </tr> <tr> <td>GGUSTAFS</td> <td>2015/03/24</td> </tr> <tr> <td>CHECKED BY</td> <td>DATE</td> </tr> <tr> <td>BARDEN</td> <td>2015/05/29</td> </tr> <tr> <td>APPROVED BY</td> <td>DATE</td> </tr> <tr> <td>BWOODMAN</td> <td>2015/04/03</td> </tr> </table>	DRAWN BY	DATE	GGUSTAFS	2015/03/24	CHECKED BY	DATE	BARDEN	2015/05/29	APPROVED BY	DATE	BWOODMAN	2015/04/03	TITLE	RJ45 TO RJ45 CORDSET RJ45 ST / RJ45 ST #26/4 TEAL TPE	
			mm	INCH																																
		4 PLACES	±---	±---																																
3 PLACES	±---	±.005																																		
2 PLACES	±.13	±.010																																		
1 PLACE	±.25	±.020																																		
DRAWN BY	DATE																																			
GGUSTAFS	2015/03/24																																			
CHECKED BY	DATE																																			
BARDEN	2015/05/29																																			
APPROVED BY	DATE																																			
BWOODMAN	2015/04/03																																			
							MOLEX INCORPORATED																													
					MATERIAL NO. SEE TABLE	DOCUMENT NO. SD-120108-079	SHEET NO. 2 OF 2																													
					SIZE B	THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION																														