



Series 222U

6.1 x 6.1mm IP67 Rated Tactile Switch

- Standard through hole configurations
- Compatible with wave, and manual soldering
- IP67 protection
- Excellent tactile feel



Ordering Information

Series	Terminal Type	Actuating Direction	Actuator Height "L"	Actuation Force
222U	D	V	A	A

Code	Spec.
D	Standard through hole

Code	Spec.
V	Vertical

Code	Spec.
A	4.3mm

Code	Spec.
A	260 gf, black



Electrical Specifications



Parameter	Conditions & Remarks	Min	Max	Unit
Contact Resistance			100	milliohms
Insulation Resistance	Between insulated terminals	100		megohms
Dielectric Strength	250 VAC between adjacent switches		1	minute
Nonswitching Rating			50 or 12	mA or VDC

Mechanical and Environmental


Soldering	Maximum wave temperature, 260°C for 5 seconds Maximum manual temperature, 350°C for 3 seconds
RoHS	Lead-Free. Fully compliant to RoHS Directive 2011/65/EU
Operating Force	260±50 gf
Actuation Life	50,000 cycles
Actuator Strength	2 Kgf maximum
Travel	0.3±0.1mm
Packaging	Bulk pack
Operating Temperature Range	-40°C to +85°C
Storage Temperature Range	-40°C to +85°C
Ingress Protection	IP67

Mechanical Specifications



Figure 1 – 222UDV, Standard Though Hole, Actuator Height 5.0mm



CIRCUIT DIAGRAM



PCB LAYOUT



DIMENSION : mm
 STANDARD TOLERANCE :
 .X (1 PLACE) : ±0.2