



used for: DIN 41651



POS.	B ±0.2	Part-NO.
10	17.30	140X10059X
14	22.40	140X10069X
16	24.90	140X10079X
20	30.00	140X10089X
26	37.60	140X10099X
34	47.80	140X10109X
40	55.40	140X10119X
50	68.10	140X10129X
60	80.80	140X10139X
64	85.85	140X10159X



APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	
CUSTOMER APPROVAL DATE:	
NAME:	TITLE:
COMPANY NAME:	
APPROVAL # FREIGABE # DEBLOCAGE # AUTORIZACION # APPROVAL	

NOTES:

- INSULATORS: PBT GV, V0, UL 94, GREY RAL 7035
- OPERATING TEMPERATURE RANGE: -55°C TO +125°C

THIS DRAWING MAY NOT BE COPIED OR REPRODUCED IN ANY WAY, AND MAY NOT BE PASSED ON TO A THIRD PARTY WITHOUT WRITTEN PERMISSION.
 OWNERSHIP AND COPYRIGHT OF CONEC GmbH
 DO NOT ALTER CAD DRAWING BY HAND

			tolerance		scale: 2:1
			2002	date	name
			drawn	11.12.	Parei
			appd.	11.12.	Kühle
			norm	DIN 41651	
			d-old		
			CONEC®		
rev.	description	date	name		

material: SEE NOTES	
title: STRAIN RELIEF 10-64pos.	
dwg no: 14K1A013	AutoCAD 2000
part no: SEE TABLE	
DIN-A 4	sh: 1/1