

## Solid-state relays - ST-OV3- 24DC/400AC/3 - 2905417

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Plug-in power solid-state relay, input: 24 V DC, output: 24 - 420 V AC/max. 3 A


The illustration shows version ST-OV  
3- 5 DC/240 AC/3

### Product Features

- Plug-in
- Control of 230 V motors in simple reversing mode (e.g., synchronous motor in single-phase mode, see illustration)
- Switching of up to 400 V AC/3 A



### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 079406
Weight per Piece (excluding packing)	62.8 GRM
Custom tariff number	85364190
Country of origin	Germany

### Technical data

#### Dimensions

Width	20.8 mm
Height	42.5 mm
Depth	112 mm

#### Ambient conditions

Ambient temperature (operation)	0 °C ... 60 °C
Ambient temperature (storage/transport)	0 °C ... 70 °C

## Solid-state relays - ST-OV3- 24DC/400AC/3 - 2905417

### Technical data

#### Input data

Nominal input voltage $U_N$	24 V DC $\pm 10\%$
Switching threshold "0" signal in reference to $U_N$	$\leq 0.4$
Switching threshold "1" signal in reference to $U_N$	$\geq 0.8$
Typical input current at $U_N$	7 mA
Operating voltage display	Yellow LED
Type of protection	Protection against polarity reversal
	RC element
Protective circuit/component	RC element
Transmission frequency	10 Hz

#### Output data

Output nominal voltage	400 V AC
Output voltage range	24 V AC ... 420 V AC
Limiting continuous current	3 A (see derating curve)
Maximum inrush current	125 A ( $t = 10$ ms)
Min. load current	50 mA
Leakage current	approx. 12 mA
Surge current	125 A ( $t = 10$ ms)
Peak offstate voltage	800 V (Periodic peak reverse voltage)
Voltage drop at max. limiting continuous current	$\leq 1.2$ V
Type of protection	Surge protection
	RC element
Protective circuit/component	Varistor
	RC element

#### General

Test voltage input/output	2.5 kV AC
	2.5 kV AC
Mounting position	Horizontal DIN rail
Standards/regulations	IEC 60664
	EN 50178
	IEC 62103
Rated surge voltage / insulation	Basic insulation
Pollution degree	2
Surge voltage category	III

## Solid-state relays - ST-OV3- 24DC/400AC/3 - 2905417

### Classifications

#### eCl@ss

eCl@ss 4.0	27371102
eCl@ss 4.1	27371102
eCl@ss 5.0	27371001
eCl@ss 5.1	27371001
eCl@ss 6.0	27371001
eCl@ss 7.0	27371001
eCl@ss 8.0	27371001

#### ETIM

ETIM 2.0	EC001504
ETIM 3.0	EC001504
ETIM 4.0	EC001504
ETIM 5.0	EC001504

#### UNSPSC

UNSPSC 6.01	30211916
UNSPSC 7.0901	39121542
UNSPSC 11	39121542
UNSPSC 12.01	39121542
UNSPSC 13.2	39121542

### Approvals

#### Approvals

---

Approvals

GOST / GOST

---

Ex Approvals

---

Approvals submitted

---

Approval details


# Solid-state relays - ST-OV3- 24DC/400AC/3 - 2905417

## Approvals




## Drawings

Diagram




- ① In rows with zero spacing
- ② stand-alone device

Diagram



## Solid-state relays - ST-OV3- 24DC/400AC/3 - 2905417

Circuit diagram



Catalog photo




Figure may contain other products.