

Extension Unit 15" KP36 PN for mounting on all fully IP65-enclosed 16:9 HMI/IPC devices. Without free installation positions. Connection via PROFINET



General information	
Product type designation	Extension Unit 15" KP36 PN
Control elements	
Version of actuating element	3x Key Panel 12
Operating principle of the actuating element	Tactile feedback
Functional lighting	Yes; Freely configurable colors: Red, green, blue, white, yellow
With parameterizable keys	Yes
Connection type	
<ul style="list-style-type: none"> <li>Connection type of the safety-related contacts (emergency stop)</li> </ul>	8-pin connector
Installation type/mounting	
Mounting	For mounting on a 16:9 HMI / IPC PRO device (lower part)
Mounting type	Screwed joint
Rack mounting	No
Front mounting	No
Number of slots for command devices and signaling units	0
RFID reader can be installed	No
Supply voltage	
Type of supply voltage	DC
Rated value (DC)	24 V
permissible range, lower limit (DC)	19.2 V
permissible range, upper limit (DC)	28.8 V
Input current	
Current consumption (rated value)	150 mA; without load
Power	
Active power input, typ.	3.6 W; Additional 2.6 W per KP12
Interfaces	
Number of industrial Ethernet interfaces	2; For the construction of lines and rings without external switch
Number of PROFINET interfaces	2; Incl. switch
Protocols	
PROFINET	Yes
Redundancy mode	
Media redundancy	
— MRP	Yes
Degree and class of protection	
IP (all-round)	IP65
Standards, approvals, certificates	
CE mark	Yes

UL approval	Yes
cULus	Yes
RCM (formerly C-TICK)	Yes
KC approval	Yes
EAC (formerly Gost-R)	Yes; EAC
Suitable for safety functions	Yes; e.g. installation of emergency stop
<b>Ambient conditions</b>	
Ambient temperature during operation	
• min.	0 °C
• max.	50 °C
Ambient temperature during storage/transportation	
• min.	-20 °C
• max.	60 °C
Altitude during operation relating to sea level	
• Installation altitude above sea level, max.	2 000 m
Relative humidity	
• Operation, max.	90 %; no condensation
<b>Cables</b>	
Cable length	30 m; Max. for emergency stop
<b>Mechanics/material</b>	
Material	
• Aluminum	Yes
Enclosure material (front)	
• Aluminum	Yes; Knockout covered with black film
<b>Dimensions</b>	
Width	396 mm
Height	99 mm
Depth	100.65 mm
<b>Weights</b>	
Weight (without packaging)	2.5 kg
<b>Scope of supply</b>	
Delivery quantity in pieces	1
Components included	Power supply connectors and 8-pole plug-in connectors for safety-related inputs

**last modified:** 4/21/2021 