

Product data sheet

Specifications



Netshelter RX 42U Enclosure 600mm x 1000mm

NSYSFRSEDC206100

Overview

Presentation	NEMA 12 rated assembled enclosure for OT, IT and networking applications. Form factor to easily roll through doorways. Configurable to work as a ventilated enclosure with the addition of Climasys ventilation components. Includes: Front and rear solid doors with handle and insert key, side panels, 19" uprights, bottom plinth, grounding and gland plate at the bottom panel. Ventilation system not included. Can be shipped pre-integrated with UPS, PDU, monitoring components and internal equipment up to 350 lbs
---------------------	--

Lead time	Usually Ships within 4 Weeks
------------------	------------------------------

Physical

Height	2100 mm
Width	600 mm
Depth	1000 mm
Number of rack unit	42U
Product weight	164 kg
Mounting mode	Rack-mounted
Mounting preference	No preference
Maximum mounting depth	852 mm
Max CTO ship weight	189 kg
Permanent permissible load	113 kg dynamic 400 kg static

Packing Units

Unit Type of Package 1	PCE
Number of Units in Package 1	1
Package 1 Height	228.0 cm
Package 1 Width	74.0 cm
Package 1 Length	116.0 cm
Package 1 Weight	224.0 kg

Offer Sustainability

EU RoHS Directive	Not applicable, out of EU RoHS legal scope
--------------------------	--

Recommended replacement(s)