



SENTRON, Molded case switch 3LD5 UL, Emergency switching-off, 4-pole, certified according to UL489 UL60947-4-1 and IEC60947-3, UL: 150A, SCCR 50kA at 480VAC, Operating power at 480VAC 3-phase: 100hp, IEC: 160A, Operating power at AC-23A at 400V: 75kW, floor mounting with door coupling rotary operating mechanism, defeatable, emergency switching-off, 4-hole mounting of the handle, without tolerance compensation, incl. terminal covers for the infeed side

| Model | |
|---|--|
| product brand name | SENTRON |
| product designation | 3LD UL switch disconnecter |
| design of the product | EMERGENCY-STOP switch |
| display version / for switch position indicator manual operation | 1 ON - 0 OFF |
| design of the actuating element | door-coupling rotary operating mechanism |
| design of handle | rotary operating mechanism, red/yellow |
| type of the driving mechanism / motor drive | No |
| General technical data | |
| number of poles | 4 |
| type of device | fixed mounting |
| type of switch | Floor mounting with door coupling |
| size of switch disconnecter | 3 |
| mechanical service life (switching cycles) / typical | 100 000 |
| electrical endurance (switching cycles) | |
| • at AC-23 A / at 690 V | 6 000 |
| I ² t value / with closed switch / at 690 V / for combination switch + gG fuse / maximum | 223 kA ² .s |
| let-through I ² t value / with closed switch / at 440 V / for combination switch + gG fuse / maximum | 223 kA ² .s |
| operating frequency / maximum | 50 1/h |
| Voltage | |
| insulation voltage / rated value | 690 V |
| surge voltage resistance / rated value | 6 kV |
| Protection class | |
| protection class IP | IP65 |
| degree of protection NEMA rating | 1, 3R, 4X, 12 |
| protection class IP / on the front | IP65 |
| Dissipation | |
| power loss [W] | |
| • for rated value of the current / at AC / in hot operating state / per pole | 36 W |
| • per conductor / typical | 36 W |
| Current | |
| operational current | |
| • at 40 °C / rated value | 160 A |
| • at 45 °C / rated value | 160 A |
| • at 50 °C / rated value | 160 A |
| • at 55 °C / rated value | 160 A |

| | |
|---|---------------------------------|
| <ul style="list-style-type: none"> • at AC / rated value | 160 A |
| <ul style="list-style-type: none"> • at AC-23 A / at 400 V / rated value | 160 A |
| <ul style="list-style-type: none"> • at AC-21 / at 690 V / rated value | 160 A |
| <ul style="list-style-type: none"> • at AC-21 A / at 240 V / rated value | 160 A |
| <ul style="list-style-type: none"> • at AC-21 A / at 440 V / rated value | 160 A |
| operational current / of upstream fuse / rated value | 160 A |
| let-through current / with closed switch | |
| <ul style="list-style-type: none"> • at 440 V / for combination switch + gG fuse / maximum | 16 kA |
| <ul style="list-style-type: none"> • at 690 V / for combination switch + gG fuse / maximum permissible | 15 kA |
| Main circuit | |
| operating power | |
| <ul style="list-style-type: none"> • at AC-23 A / at 240 V / rated value | 45 kW |
| <ul style="list-style-type: none"> • at AC-23 A / at 440 V / rated value | 75 kW |
| <ul style="list-style-type: none"> • at AC-23 A / at 690 V / rated value | 55 kW |
| <ul style="list-style-type: none"> • at AC-3 / at 240 V / rated value | 45 kW |
| <ul style="list-style-type: none"> • at AC-3 / at 400 V / rated value | 75 kW |
| <ul style="list-style-type: none"> • at AC-3 / at 690 V / rated value | 45 kW |
| operational current / rated value | 160 A |
| Auxiliary circuit | |
| number of CO contacts / for auxiliary contacts | 0 |
| number of NC contacts / for auxiliary contacts | 0 |
| number of NO contacts / for auxiliary contacts | 0 |
| operating voltage / of auxiliary contacts / at AC / maximum | 500 V |
| continuous current / of the auxiliary contact / rated value | 10 A |
| insulation voltage / of the auxiliary switch / rated value | 500 V |
| Suitability | |
| suitability for use | |
| <ul style="list-style-type: none"> • main switch | Yes |
| <ul style="list-style-type: none"> • switch disconnecter | Yes |
| <ul style="list-style-type: none"> • EMERGENCY OFF switch | Yes |
| <ul style="list-style-type: none"> • safety switch | Yes |
| <ul style="list-style-type: none"> • maintenance/repair switch | Yes |
| Appearance | |
| color / of the actuating element | red |
| Product details | |
| product feature | |
| <ul style="list-style-type: none"> • can be locked into OFF position | Yes |
| number of bracket locks / maximum | 3 |
| hasp thickness / of the bracket locks / minimum | 5 mm |
| hasp thickness / of the bracket locks / maximum | 7.5 mm |
| special product feature | defeatable door-coupling handle |
| product extension / optional | |
| <ul style="list-style-type: none"> • motor drive | No |
| <ul style="list-style-type: none"> • voltage trigger | No |
| Short circuit | |
| conditional short-circuit current / with line-side fuse protection | |
| <ul style="list-style-type: none"> • at 440 V / by gG fuse / rated value | 50 kA |
| <ul style="list-style-type: none"> • at 690 V / by gG fuse / rated value | 30 kA |
| according UL | |
| operational current / at AC / according to UL 489/UL 60947-4-1 / rated value | 150 A |
| operational current / at AC / according to UL 508/UL 60947-4-1 / rated value | 150 A |
| operating voltage / at AC / at 50/60 Hz / according to UL 489 / rated value | 480 V |
| operating voltage / at AC / at 50/60 Hz / according to UL 508/UL 60947-4-1 / rated value | 480 V |
| active power [hp] / at AC / at 480 V / according to UL | 100 |

| | |
|---|--|
| 508/UL 60947-4-1 / rated value | |
| short-time withstand current (SCCR) / at 480 V / according to UL 508/UL 60947-4-1 and UL 489 | 50 kA |
| continuous current / of upstream fuse / according to UL / rated value | 150 A |
| type of fuse / according to UL | Class J |
| Number | |
| number of connectable NC contacts / for auxiliary contacts / attachable / maximum | 2 |
| number of connectable NO contacts / for auxiliary contacts / attachable / maximum | 3 |
| number of connectable CO contacts / for auxiliary contacts / attachable / maximum | 0 |
| Connections | |
| AWG number / as coded connectable conductor cross section / solid | |
| • minimum | 1 |
| • maximum | 4/0 |
| AWG number / as coded connectable conductor cross section / solid / according to UL 489 | |
| • minimum | 1 |
| AWG number / as coded connectable conductor cross section / solid / according to CSA C22.2 No. 5-16 | |
| • minimum | 3 |
| type of connectable conductor cross-sections / for copper conductor | |
| • solid | 1x (16 ...185mm ²) |
| • finely stranded / with core end processing | 1x (16...150mm ²) |
| • stranded | 1x (16...185mm ²) |
| type of connectable conductor cross-sections / for auxiliary contacts | |
| • solid | lateral auxiliary switch 2x (0,75 ... 2,5mm ²), 1x 4mm ² ; front auxiliary switch 1x (0,75 ... 2,5mm ²) |
| • finely stranded / with core end processing | lateral auxiliary switch 2x (0,75 ... 1,5mm ²), 1x 2,5mm ² ; front auxiliary switch 1x 2,5mm ² |
| • stranded | lateral auxiliary switch 2x (0,75 ... 2,5mm ²), 1x 4mm ² ; front auxiliary switch 1x (0,75 ... 2,5mm ²) |
| type of electrical connection | |
| • for main current circuit | box terminal |
| • for auxiliary contacts | connection terminals |
| Requirements | |
| design of the fuse link | |
| • for short-circuit protection of the main circuit / required | Fuse gG: 160 A |
| • for short-circuit protection of the auxiliary switch / required | fuse gL/gG: 10 A |
| Mechanical Design | |
| height | 178 mm |
| width | 151 mm |
| depth | 158 mm |
| fastening method | Built-in unit fixed-mounted version |
| fastening method | |
| • 4-hole front mounting | Yes |
| • front mounting with central attachment | No |
| • rail mounting | No |
| net weight | 2 400 g |
| Environmental conditions | |
| ambient temperature / during operation | |
| • minimum | -25 °C |
| • maximum | 55 °C |
| ambient temperature / during storage / minimum | -25 °C |
| General Product Approval | |
| Declaration of Conformity | |



[Confirmation](#)



other

[Miscellaneous](#)

Further information

Information- and Downloadcenter (Catalogs, Brochures,...)

<http://www.siemens.com/lowvoltage/catalogs>

Industry Mall (Online ordering system)

<https://mall.industry.siemens.com/mall/en/en/Catalog/product?mlfb=3LD5810-0TL13>

Service&Support (Manuals, Certificates, Characteristics, FAQs,...)

<https://support.industry.siemens.com/cs/ww/en/ps/3LD5810-0TL13>

Image database (product images, 2D dimension drawings, 3D models, device circuit diagrams, ...)

http://www.automation.siemens.com/bilddb/cax_en.aspx?mlfb=3LD5810-0TL13

CAX-Online-Generator

<http://www.siemens.com/cax>

Tender specifications

<http://www.siemens.com/specifications>



