# 5-146257-3 ACTIVE

#### AMPMODU | AMPMODU Headers

TE Internal #: 5-146257-3

PCB Mount Header, Vertical, Board-to-Board, 6 Position, 2.54 mm [. 1 in] Centerline, Breakaway, Gold, Through Hole - Solder, Signal,

AMPMODU Headers

View on TE.com >



Connectors > PCB Connectors > PCB Headers & Receptacles

PCB Connector Assembly Type: PCB Mount Header

PCB Mount Orientation: Vertical
Connector System: Board-to-Board

Number of Positions: 6
Number of Rows: 2

#### **Features**

#### **Product Type Features**

PCB Connector Assembly Type	PCB Mount Header	
Connector System	Board-to-Board	
Header Type	Breakaway	
Sealable	No	
Connector & Contact Terminates To	Printed Circuit Board	

### **Configuration Features**

Connector Contact Load Condition	Fully Loaded
PCB Mount Orientation	Vertical
Number of Positions	6
Number of Rows	2
Board-to-Board Configuration	Parallel

# **Electrical Characteristics**

	Operating Voltage	30 VAC
--	-------------------	--------

# **Body Features**

Connector Profile	Standard
Primary Product Color	Black

#### **Contact Features**

Mating Square Post Dimension	.64 mm[.025 in]
	100 – 200 μin



PCB Contact Termination Area Plating Material Finish	Matte	
Contact Shape & Form	Square	
Contact Underplating Material	Nickel	
PCB Contact Termination Area Plating Material	Tin	
Contact Base Material	Phosphor Bronze	
Contact Mating Area Plating Material	Gold	
Contact Mating Area Plating Material Thickness	.762 μm[30 μin]	
Contact Type	Pin	
Contact Current Rating (Max)	3 A	
Termination Features		
Square Termination Post & Tail Dimension	.64 mm[.025 in]	
Termination Post & Tail Length	3.05 mm[.12 in]	
Termination Method to Printed Circuit Board	Through Hole - Solder	
Mechanical Attachment		
Mating Alignment	Without	
PCB Mount Retention	Without	
PCB Mount Alignment	Without	
Connector Mounting Type	Board Mount	
Housing Features		
Centerline (Pitch)	2.54 mm[.1 in]	
Housing Material	Thermoplastic	
Dimensions		
Row-to-Row Spacing	2.54 mm[.1 in]	
PCB Thickness (Recommended)	1.57 mm[.062 in]	
Usage Conditions		
Housing Temperature Rating	High	
Operating Temperature Range	-65 – 105 °C[-85 – 221 °F]	
Operation/Application		
Solder Process Feature	Board Standoff	
Circuit Application	Signal	
Industry Standards		
Approved Standards	CSA LR7189, UL E28476	



UL Flammability Rating UL 94V-0

#### **Packaging Features**

Packaging Quantity	520
Packaging Type	Carton

# **Product Compliance**

For compliance documentation, visit the product page on TE.com>

EU RoHS Directive 2011/65/EU	Compliant	
EU ELV Directive 2000/53/EC	Compliant	
China RoHS 2 Directive MIIT Order No 32, 2016	No Restricted Materials Above Threshold	
EU REACH Regulation (EC) No. 1907/2006	Current ECHA Candidate List: JUNE 2023 (235) Candidate List Declared Against: JAN 2023 (233) Does not contain REACH SVHC	
Halogen Content	Low Bromine/Chlorine - Br and Cl < 900 ppm per homogenous material. Also BFR /CFR/PVC Free	
Solder Process Capability	Pin-in-Paste capable to 260°C	

#### Product Compliance Disclaimer

This information is provided based on reasonable inquiry of our suppliers and represents our current actual knowledge based on the information they provided. This information is subject to change. The part numbers that TE has identified as EU RoHS compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, mercury, PBB, PBDE, DBP, BBP, DEHP, DIBP, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2011/65/EU (RoHS2). Finished electrical and electronic equipment products will be CE marked as required by Directive 2011/65/EU. Components may not be CE marked. Additionally, the part numbers that TE has identified as EU ELV compliant have a maximum concentration of 0.1% by weight in homogenous materials for lead, hexavalent chromium, and mercury, and 0.01% for cadmium, or qualify for an exemption to these limits as defined in the Annexes of Directive 2000/53/EC (ELV). Regarding the REACH Regulation, the information TE provides on SVHC in articles for this part number is based on the latest European Chemicals Agency (ECHA) 'Guidance on requirements for substances in articles' posted at this URL: https://echa.europa.eu/guidance-documents/guidance-on-reach

# Compatible Parts

TE Part # 5-534206-3 06 MODII VRT DR CE 100/115

TE Part # 6-5535512-2 06 MODII HORZ DR CE EESS .100 TE Part # 5147722-2 06 MODII HORZ DR SFMNT 30AU



Also in the Series	AMPMODU Hea	ders	
PCB Connector Mounting(1)	PCB Connector Shrouds(1)	PCB Headers & Receptacles(4875)	PCB Latches, Locks & Retainers(1)
Wire-to-Board Connector Assemblies & Housings(5)  Customers Also Bo	Wire-to-Board Connector Contacts(65)		
TE Part #917725-1 2.5 SIGNAL D/LOCK HDR ASSY 5P	TE Part #5-146257-4 08 MODII HDR DRST B/A .100CL L	TE Part #1623719-8 CCR1 10R 10%	TE Part #2176338-7 CRGCQ 0402 10R 5%
TE Part #927837-4 SPT REC 6.3 Contact SRC Ag	TE Part #2-1415521-1 RFH54012WG	TE Part #234486-E SRCA 1,27 12 F 1 I2426 137 E1 094 1,07 T	

#### Documents

**CAD Files** 

3D PDF

3D

Customer View Model

ENG\_CVM\_CVM\_5-146257-3\_J.2d\_dxf.zip

English

PCB Mount Header, Vertical, Board-to-Board, 6 Position, 2.54 mm [.1 in] Centerline, Breakaway, Gold, Through Hole - Solder, Signal, AMPMODU Headers



**Customer View Model** 

ENG\_CVM\_CVM\_5-146257-3\_J.3d\_igs.zip

English

**Customer View Model** 

ENG\_CVM\_CVM\_5-146257-3\_J.3d\_stp.zip

English

By downloading the CAD file I accept and agree to the **Terms and Conditions** of use

**Product Environmental Compliance** 

Product Compliance Document

English

**Product Compliance Document** 

English