

A. System Overview

B1. Cable Ties

B2. Cable Accessories

B3. Stainless Steel Ties

C1. Wiring Duct

C2. Surface Raceway

C3. Abrasion Protection

C4. Cable Management

D1. Terminals

D2. Power Connectors

D3. Grounding Connectors

E1. Labeling Systems

E2. Labels

E3. Pre-Printed & Write-On Markers

E4. Permanent Identification


E5. Lockout/Tagout & Safety Solutions

F. Index

## Grounding Clamp for Water Pipes, Aluminum

### Type GC

- Dual-rated for grounding aluminum or copper code conductors to copper water pipe, galvanized pipe, or steel conduit
- Made from high strength, extruded aluminum alloy to provide long term durability
- Tin-plated to inhibit corrosion and oxidation and for low contact resistance
- Plated steel screws provide high strength and inhibit corrosion
- Accommodates a wide range of pipe, tube, and conductor sizes – minimizes inventory requirements
- UL Listed for grounding and bonding




| Part Number     | Conduit Pipe or Water Tube Size | Conductor Size Range | Figure Dimensions In. (mm) |             | Std. Pkg. Qty. |
|-----------------|---------------------------------|----------------------|----------------------------|-------------|----------------|
|                 |                                 |                      | L                          | W           |                |
| <b>GC-15A-Q</b> | 1/2 – 3/4 – 1                   | #14 AWG – 1/0 AWG    | 2.25 (57.2)                | 0.69 (17.5) | 25             |
| <b>GC-18A-X</b> | 1 1/4 – 1, 1/2 – 2              | #6 AWG – 250 kcmil   | 3.75 (95.3)                | 0.81 (20.6) | 10             |
| <b>GC-22A-4</b> | 2 1/2 – 3 – 3 1/2 – 4           | #6 AWG – 250 kcmil   | 6.31 (95.3)                | 1.00 (25.4) | 4              |

## Grounding Rod Clamp, Bronze

### Type WB

- Used for grounding copper conductor parallel to ground rods
- Made from high strength, seamless electrolytic bronze to provide long term durability
- High strength silicon bronze hardware provides long term reliable assembly
- Accommodates a wide range of rod and conductor sizes – minimizes inventory requirements
- UL Listed and CSA Certified for grounding and bonding and suitable for direct burial in earth and concrete



| Part Number   | Ground Rod Size | Conductor Size Range         | Figure Dimensions In. (mm) |             |             | Hex Size In. | Std. Pkg. Qty. |
|---------------|-----------------|------------------------------|----------------------------|-------------|-------------|--------------|----------------|
|               |                 |                              | L                          | W           | H           |              |                |
| <b>WB12-L</b> | 1/2             | #2 – #10 STR, #10 SOL        | 0.88 (22.4)                | 0.84 (21.3) | 1.28 (32.5) | 1/2          | 50             |
| <b>WB34-X</b> | 5/8<br>3/4      | 1/0 – #8 STR,<br>#2 – #8 STR | 1.03 (26.2)                | 1.06 (26.9) | 1.54 (39.1) | 1/2          | 10             |
| <b>WB58-Q</b> | 5/8             | 1/0 – #8 STR                 | 1.04 (26.4)                | 0.92 (23.4) | 1.40 (35.6) | 1/2          | 25             |