

## Surge protection base element - UFBK 2-PE- 5DC-HF-BE - 2781262


Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)

Base element for protective plug UFBK 2-PE -5 V DC-HF-ST, with universal foot for mounting on NS 35 or NS 35/7.5, nominal voltage: 5 V DC

### Product description

Base element to accept a protective plug: UFBK 2-PE-5DC-HF-ST.

### Key commercial data

Packing unit	1 pc
GTIN	 4 017918 068899
Weight per Piece (excluding packing)	54.11 GRM
Custom tariff number	85363010
Country of origin	Germany

### Technical data

#### Dimensions

Horizontal pitch	1 Div.
------------------	--------

#### Ambient conditions

Ambient temperature (operation)	-20 °C ... 60 °C
Degree of protection	IP20

#### General

Stripping length	8 mm
Conductor cross section stranded min.	0.2 mm <sup>2</sup>
Conductor cross section stranded max.	2.5 mm <sup>2</sup>
Conductor cross section solid min.	0.2 mm <sup>2</sup>
Conductor cross section solid max.	4 mm <sup>2</sup>
Conductor cross section AWG/kcmil min.	24
Conductor cross section AWG/kcmil max	12
Nominal current I <sub>N</sub>	200 mA
Housing material	PA
Inflammability class according to UL 94	V2

## Surge protection base element - UFBK 2-PE- 5DC-HF-BE - 2781262

### Classifications

#### eCl@ss

eCl@ss 4.0	27140201
eCl@ss 4.1	27130801
eCl@ss 5.0	27130801
eCl@ss 5.1	27130801
eCl@ss 6.0	27130803

#### ETIM

ETIM 2.0	EC000472
ETIM 3.0	EC000472
ETIM 4.0	EC000472

#### UNSPSC

UNSPSC 6.01	30212010
UNSPSC 7.0901	39121610
UNSPSC 11	39121610
UNSPSC 13.2	39121620