



12.55 ±0.15
 $\phi 3_{-0.10}^0$

$\phi 3.8$ EYE OF THE NEEDLE

12.69 ±0.1

G
 2.90
 4.40 UNC
 6.30 ±0.1
 8.08 ±0.1
 2.84 ±0.25

Detail of grounding strip

90° ±0.2
 2.90 ±0.2
 9.50 ±0.1

D
 2.76 shell 25-37
 2.74 shell 9-15
 1.38 shell 25-37
 1.37 shell 9-15
 8.35 ±0.12
 PITCH ±0.25

PC card drilling dimensions(after plating)
 (thickness 1.60 or 2.40 ±0.20mm)

Pitch 2.76(shell 25-37)
 Pitch 2.74(shell 09-15)
 $\phi 0.13$ ϕA
 $\phi 0.13$ ϕB
 1.37(shell 09-15)
 1.38(shell 25-37)
 E
 B
 1.42
 1.42

TIN LEAD PART NUMBER

SHELL	A±0.38	B±0.12	C±0.10	D +0.25	E±0.07	G	PART NUMBER	PART NUMBER
09	30.81	24.99	18.00	16.79	10.96	5.90 +0.15	D09P80C4GV00	D09P80C6GV00
15	39.14	33.32	26.32	25.12	19.18	5.90 +0.15	D15P80C4GV00	D15P80C6GV00
25	53.03	47.04	40.04	38.84	33.12	5.70 +0.25	D25P80C4GV00	D25P80C6GV00
37	69.32	63.50	56.50	55.30	49.68	5.70 +0.25	D37P80C4GV00	D37P80C6GV00
							Gold flash	0,76 » gold

LEAD FREE PART NUMBER

SHELL	A±0.38	B±0.12	C±0.10	D +0.25	E±0.07	G	PART NUMBER	PART NUMBER
09	30.81	24.99	18.00	16.79	10.96	5.90 +0.15	D09P80C4GV00LF	D09P80C6GV00LF
15	39.14	33.32	26.32	25.12	19.18	5.90 +0.15	D15P80C4GV00LF	D15P80C6GV00LF
25	53.03	47.04	40.04	38.84	33.12	5.70 +0.25	D25P80C4GV00LF	D25P80C6GV00LF
37	69.32	63.50	56.50	55.30	49.68	5.70 +0.25	D37P80C4GV00LF	D37P80C6GV00LF
							Gold flash	0,76 » gold

GENERAL CHARACTERISTICS AND ROHS INFORMATIONS:

SEE DRAWING C01-8646-0001

mat'l. code		surface		tolerance		projection		product family	
-		ISO 1302		ISO 406 ISO 1101				D-SUB	
ltr		ecn no		dr		date		title	
H		ELX-I-17859		MP		2014/06/06		MALE CONNECTOR DELTA-D US RIGHT ANGLED PRESS FIT	
								dwg no	
								sheet 1 of 1	
								size	
								A3	
								type	
								Product Customer Drawing	
sheet		revision		H					
index		sheet		1					

