


## Features

- Low On-Resistance
  - 95mΩ @V<sub>GS</sub> = -4.5V
  - 120mΩ @V<sub>GS</sub> = -2.5V
  - 86mΩ (typ) @V<sub>GS</sub> = -1.8V
- Low Gate Threshold Voltage, -1.3V Max
- Fast Switching Speed
- Low Input/Output Leakage
- Incorporates Low V<sub>F</sub> Super Barrier Rectifier (SBR)
- Low Profile, 0.5mm Max Height
- **Lead Free/RoHS Compliant (Note 2)**
- **"Green" Device (Note 3)**
- **Qualified to AEC-Q101 Standards for High Reliability**


## Mechanical Data

- Case: DFN3020-8
- Case Material: Molded Plastic, "Green" Molding Compound. UL Flammability Classification Rating 94V-0
- Moisture Sensitivity: Level 1 per J-STD-020D
- Terminal Connections: See Diagram
- Terminals: Finish – NiPdAu over Copper leadframe. Solderable per MIL-STD-202, Method 208
- Marking Information: See Page 5
- Ordering Information: See Page 5
- Weight: 0.011 grams (approximate)



DFN3020-8



Top View



Bottom View


 Top View  
Internal Schematic

 Bottom View  
Pin Configuration

## Maximum Ratings – TOTAL DEVICE @T<sub>A</sub> = 25°C unless otherwise specified

Characteristic	Symbol	Value	Unit
Power Dissipation (Note 1)	P <sub>D</sub>	1.5	W
Thermal Resistance, Junction to Ambient	R <sub>θJA</sub>	85	°C/W
Operating and Storage Temperature Range	T <sub>J</sub> , T <sub>STG</sub>	-55 to +150	°C

## Maximum Ratings – P-CHANNEL MOSFET – Q1 @T<sub>A</sub> = 25°C unless otherwise specified

Characteristic	Symbol	Value	Units
Drain-Source Voltage	V <sub>DSS</sub>	-20	V
Gate-Source Voltage	V <sub>GS</sub>	±12	V
Drain Current (Note 1)	I <sub>D</sub>	-2.9	A
Pulsed Drain Current (Note 4)	I <sub>DM</sub>	-10	A

## Maximum Ratings – SBR – D1 @T<sub>A</sub> = 25°C unless otherwise specified

Characteristic	Symbol	Value	Unit
Peak Repetitive Reverse Voltage	V <sub>RRM</sub>	35	V
Working Peak Reverse Voltage	V <sub>RWM</sub>		
DC Blocking Voltage	V <sub>R</sub>		
RMS Reverse Voltage	V <sub>R(RMS)</sub>	25	V
Average Rectified Output Current	I <sub>O</sub>	1	A
Non-Repetitive Peak Forward Surge Current 8.3ms single half sine-wave superimposed on rated load	I <sub>FSM</sub>	3	A

- Notes:
1. Device mounted on FR-4 PCB, on minimum recommended, 2oz Copper pad layout.
  2. No purposefully added lead.
  3. Diodes Inc.'s "Green" policy can be found on our website at [http://www.diodes.com/products/lead\\_free/index.php](http://www.diodes.com/products/lead_free/index.php).
  4. Repetitive rating, pulse width limited by junction temperature.

SBR is a registered trademark of Diodes Incorporated.

DMS2220LFW

Document number: DS31547 Rev. 8 - 2

1 of 6

[www.diodes.com](http://www.diodes.com)

March 2009

© Diodes Incorporated



**Electrical Characteristics – P-CHANNEL MOSFET – Q1** @ $T_A = 25^\circ\text{C}$  unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
<b>OFF CHARACTERISTICS (Note 5)</b>						
Drain-Source Breakdown Voltage	$BV_{DSS}$	-20	—	—	V	$V_{GS} = 0V, I_D = -250\mu A$
Zero Gate Voltage Drain Current	$I_{DSS}$	—	—	-1	$\mu A$	$V_{DS} = -20V, V_{GS} = 0V$
Gate-Source Leakage	$I_{GSS}$	—	—	$\pm 100$ $\pm 800$	nA	$V_{GS} = \pm 8V, V_{DS} = 0V$ $V_{GS} = \pm 12V, V_{DS} = 0V$
<b>ON CHARACTERISTICS (Note 5)</b>						
Gate Threshold Voltage	$V_{GS(th)}$	-0.45	—	-1.3	V	$V_{DS} = V_{GS}, I_D = -250\mu A$
Static Drain-Source On-Resistance	$R_{DS(ON)}$	—	60	95	m $\Omega$	$V_{GS} = -4.5V, I_D = -2.8A$
		—	74	120		$V_{GS} = -2.5V, I_D = -2.0A$
		—	86	—		$V_{GS} = -1.8V, I_D = -1.0A$
Forward Transfer Admittance	$ Y_{fs} $	—	8	—	S	$V_{DS} = -5V, I_D = -2.8A$
Diode Forward Voltage (Note 5)	$V_{SD}$	—	0.7	-1.2	V	$V_{GS} = 0V, I_S = -1.6A$
<b>DYNAMIC CHARACTERISTICS</b>						
Input Capacitance	$C_{iss}$	—	632	—	pF	$V_{DS} = -10V, V_{GS} = 0V$ $f = 1.0\text{MHz}$
Output Capacitance	$C_{oss}$	—	65	—	pF	
Reverse Transfer Capacitance	$C_{rss}$	—	54	—	pF	

**Electrical Characteristics – SBR – D1** @ $T_A = 25^\circ\text{C}$  unless otherwise specified

Characteristic	Symbol	Min	Typ	Max	Unit	Test Condition
Reverse Breakdown Voltage (Note 5)	$V_{(BR)R}$	35	40	—	V	$I_R = 1\text{mA}$
Forward Voltage	$V_F$	—	—	0.42	V	$I_F = 0.5A$
		—	—	0.49		$I_F = 1.0A$
Reverse Current (Note 5)	$I_R$	—	—	100	$\mu A$	$V_R = 20V$

Notes: 5. Short duration pulse test used to minimize self-heating effect.

**Q1, P-CHANNEL MOSFET**


NEW PRODUCT

**Q1, P-CHANNEL MOSFET - Continued**




Fig. 3 Typical On-Resistance vs. Drain Current and Gate Voltage




Fig. 4 Typical Drain-Source On-Resistance vs. Drain Current and Temperature




Fig. 5 On-Resistance Variation with Temperature




Fig. 6 On-Resistance Variation with Temperature




Fig. 7 Typical Capacitance




Fig. 8 Gate Threshold Variation vs. Ambient Temperature

SBR is a registered trademark of Diodes Incorporated.

**Q1, P-CHANNEL MOSFET - Continued**




Fig. 9 Diode Forward Voltage vs. Current

**D1, SBR**




Fig. 10 Forward Power Dissipation




Fig. 11 Typical Forward Characteristics

**D1, SBR - Continued**




Fig. 12 Typical Reverse Characteristics




Fig. 13 Total Capacitance vs. Reverse Voltage




Fig. 14 Forward Current Derating Curve




Fig. 15 Operating Temperature Derating

**Ordering Information** (Note 6)

Part Number	Case	Packaging
DMS2220LFW-7	DFN3020-8	3000/Tape & Reel

Notes: 6. For packaging details, go to our website at <http://www.diodes.com/datasheets/ap02007.pdf>.

**Marking Information**



ME = Product Type Marking Code  
 YM = Date Code Marking  
 Y = Year (ex: V = 2008)  
 M = Month (ex: 9 = September)

Date Code Key


Year	2008	2009	2010	2011	2012	2013	2014	2015
Code	V	W	X	Y	Z	A	B	C

Month	Jan	Feb	Mar	Apr	May	Jun	Jul	Aug	Sep	Oct	Nov	Dec
Code	1	2	3	4	5	6	7	8	9	O	N	D


SBR is a registered trademark of Diodes Incorporated.

### Package Outline Dimensions



DFN3020-8			
Dim	Min	Max	Typ
A	0.77	0.83	0.80
A1	0	0.05	0.02
A3	-	-	0.15
b	0.25	0.35	0.30
D	2.95	3.075	3.00
D1	0.90	1.10	1.00
e	-	-	0.65
E	1.95	2.075	2.00
E1	0.80	1.00	0.90
L	0.30	0.40	0.35
Z	-	-	0.375
All Dimensions in mm			

### Suggested Pad Layout



Dimensions	Value (in mm)
C	0.650
G	0.600
G1	0.450
G2	0.150
R	0.150
X	0.390
X1	1.000
Y	0.550
Y1	0.900

#### IMPORTANT NOTICE

Diodes Incorporated and its subsidiaries reserve the right to make modifications, enhancements, improvements, corrections or other changes without further notice to any product herein. Diodes Incorporated does not assume any liability arising out of the application or use of any product described herein; neither does it convey any license under its patent rights, nor the rights of others. The user of products in such applications shall assume all risks of such use and will agree to hold Diodes Incorporated and all the companies whose products are represented on our website, harmless against all damages.

#### LIFE SUPPORT

Diodes Incorporated products are not authorized for use as critical components in life support devices or systems without the expressed written approval of the President of Diodes Incorporated.