



Directions: Clean floor and apply two thin coats of floor finish with a dedicated rayon mop. Wait one hour between coats. Consult application procedure for details and precise instructions.

Maintenance: Sweep or damp mop daily to remove dirt. Periodically clean with a 1:1 dilution of water and floor finish. Apply a thin top coat of floor finish every 4 – 6 weeks. For heavy cleaning, use the 4100 Restorer Cleaner. Consult maintenance procedure for details and precise instructions.

Product #40001; 4 gallons per case **Product #40005**; 5-gallon pail **Product #40002**; 54-gallon drum

4000 Staticide[®] Acrylic Floor Finish

Low Cost + High Performance = Value

Staticide[®] Acrylic Floor Finish offers high-tech static protection at a reasonable price. This economical formula leaves a durable, glossy finish that can last up to twelve months, making it a popular choice for budget-minded companies with industrial areas where static control is essential.

Easy to apply and maintain, Staticide[®] Acrylic Floor Finish leaves floors with a surface resistivity of 10⁸ -10⁹ ohms per square, complying with ANSI/ESD S20.20 guidelines. This water-based formula is UL listed for slip resistance, RoHS compliant, biodegradable, non-flammable, and free of formaldehyde, phthalates, alkalis, acids, and ammonia.

As ACL's original ESD floor finish, Staticide® Acrylic continues to be an ideal choice for production areas, warehousing, shipping, laboratories, and electronic repair facilities.

- 🕸 Coverage: 1,500 2,000 square feet per gallon
- 🕸 Non-toxic; biodegradable
- 🕸 Non-volatile solids: 20 ± 5%
- 🕸 Strip cycle: 6-12 months
- Suitable to use on vinyl, linoleum, and ceramic tiles
- Surface resistivity: 10⁸ 10⁹ ohms per square (average)
- **&** Low V.O.C.
- 🕸 Water-based acrylic

ACL**Staticide**.

840 W.49th Place · Chicago, IL 60609 800.782.8420 · 847.981.9212 · fax 847.981.9278 info@aclstaticide.com · www.aclstaticide.com



ACL Inc. registered to ISO-9001 : 2008 Certificate NO. 10002746

Rev. 08/04/14 mkb