

## **Specification Sheet**

Part Number: TAGPP1T6-822



White polyester is glossy, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Thermal Transfer Labels, 0.63" x .31", 6 Across, Polyester, White, 1000/roll

Article Number 596-00028

Type TAGPP1T6

Color White (WH)

**Quantity Per** roll

**Product Description** 

HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 822 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking.

Thermal Transfer Labels, 0.63" x .31", 6 Across, Polyester, White, **Short Description** 

1000/roll

Global F	Part Name
----------	-----------

TAGPP1T6-822-WH

Width W (Imperial)	0.625
Width W (Metric)	15.87
Bundle Diameter Min (Imperial)	.39
Bundle Diameter Min (Metric)	1.0
Bundle Diameter Max (Imperial)	0.87
Bundle Diameter Max (Metric)	22.20
Thickness T (Metric)	64.0
Height H (Imperial)	.333
Height H (Metric)	7.92
Width of Liner (Metric)	96.52
Width of Liner (Imperial)	3.80

Material Type 822, Polyester (822)

Material Shortcut 822

Adhesive Acrylic

Halogen Free	No
UV Resistant (Yes/No)	No
Adhesive Operating Temperature	-40°F to +194°F (-40°C to +90°C)
Operating Temperature	-40°F to +302°F (-40°C to +150°C)
Reach Compliant (Article 33)	Yes
ROHS Compliant	Yes
Certification/Specification	UL-Recognized
UL Recognized (US)	Yes
UL Recognized (US and Canada)	Yes
Package Quantity (Imperial)	1000
Package Quantity (Metric)	1000
Customs Number	3919102055
Labels per Column	1
Labels per Row	6

www.hellermann.tyton.com).			
2023 HellermannTyton. All Right	RoHS/WEEE Compliand	ce Disclaimer	Terms and Condition