






RoHS COMPLIANT



RECOMMENDED PCB LAYOUT



RECOMMENDED PANEL CUTOUT



Electrical Characteristics

| | |
|-------------------------------------|-----------------------------|
| Nominal Impedance: | 75 ohms |
| Frequency Range: | DC to 1 GHz |
| VSWR: | 1.3:1 maximum |
| Insertion Loss: | 0.2 dB at 4 GHz |
| Operating Voltage (rms): | 500 V maximum at sea level |
| Dielectric Withstand Voltage (rms): | 1500 V maximum at sea level |
| Contact Resistance: | 3.0 milliohms maximum |
| Insulation Resistance: | 500 megohms minimum |

Mechanical Characteristics

| | |
|-----------------------|------------------------|
| Mating Cycles: | 500 cycles minimum |
| Interface Dimensions: | Conform to MIL-C-39012 |

Environmental Characteristics

| | |
|--------------------|------------------|
| Temperature Range: | -55 °C to +85 °C |
|--------------------|------------------|

| REF. | DESCRIPTION | MATERIAL | PLATING |
|------|-----------------|-------------------|-----------------|
| 1 | Body | Zinc Alloy | Nickel |
| 2 | Insulator | Polypropylene | |
| 3 | Ground Terminal | Copper-clad steel | Tin |
| 4 | Contact | Phosphor | Gold |
| 5 | Mounting Post | Phosphor | Tin > 5 Microns |
| 6 | Lock Washer | Brass | Nickel |
| 7 | Hex Nut | Brass | Nickel |

| DESCRIPTION OF REVISION | APPVD | ISS | DATE |
|-------------------------|-------|-----|-----------|
| Dimension Updated | LB | 4 | 31 Jan 12 |
| Complete Update | KA | 3 | 17 Mar 08 |
| Plating Thickness added | MS | 2 | 15 Jan 08 |
| First Issue | SN | 1 | 09 Nov 01 |



Cinch Connectivity Solutions
7-13 Russel Way,
Widford Industrial Estate,
Chelmsford, Essex,
CM1 3AA, UK.
Tel: +44 (0) 1245 359515
Fax: +44 (0) 1245 358938

SCALE: Not To Scale

DIMENSIONS: mm

TOLERANCES:
± 0.2mm unless
otherwise stated

DRAWN BY:

S Nash

CHECKED BY:

P Couzens

APPROVED BY:

R Drennan

DATE:

09 Nov 01

TITLE:

**BNC Right Angle PCB Mount
Jack With Self Captivating
Legs**

PART NUMBER:

VBM201C-75

PAGE: 1 of 1