Old Company Name in Catalogs and Other Documents

On April 1st, 2010, NEC Electronics Corporation merged with Renesas Technology Corporation, and Renesas Electronics Corporation took over all the business of both companies. Therefore, although the old company name remains in this document, it is a valid Renesas Electronics document. We appreciate your understanding.

Renesas Electronics website: http://www.renesas.com

April 1st, 2010 Renesas Electronics Corporation

Issued by: Renesas Electronics Corporation (<u>http://www.renesas.com</u>)

Send any inquiries to <u>http://www.renesas.com/inquiry</u>.

Notice

- 1. All information included in this document is current as of the date this document is issued. Such information, however, is subject to change without any prior notice. Before purchasing or using any Renesas Electronics products listed herein, please confirm the latest product information with a Renesas Electronics sales office. Also, please pay regular and careful attention to additional and different information to be disclosed by Renesas Electronics such as that disclosed through our website.
- Renesas Electronics does not assume any liability for infringement of patents, copyrights, or other intellectual property rights of third parties by or arising from the use of Renesas Electronics products or technical information described in this document. No license, express, implied or otherwise, is granted hereby under any patents, copyrights or other intellectual property rights of Renesas Electronics or others.
- 3. You should not alter, modify, copy, or otherwise misappropriate any Renesas Electronics product, whether in whole or in part.
- 4. Descriptions of circuits, software and other related information in this document are provided only to illustrate the operation of semiconductor products and application examples. You are fully responsible for the incorporation of these circuits, software, and information in the design of your equipment. Renesas Electronics assumes no responsibility for any losses incurred by you or third parties arising from the use of these circuits, software, or information.
- 5. When exporting the products or technology described in this document, you should comply with the applicable export control laws and regulations and follow the procedures required by such laws and regulations. You should not use Renesas Electronics products or the technology described in this document for any purpose relating to military applications or use by the military, including but not limited to the development of weapons of mass destruction. Renesas Electronics products and technology may not be used for or incorporated into any products or systems whose manufacture, use, or sale is prohibited under any applicable domestic or foreign laws or regulations.
- 6. Renesas Electronics has used reasonable care in preparing the information included in this document, but Renesas Electronics does not warrant that such information is error free. Renesas Electronics assumes no liability whatsoever for any damages incurred by you resulting from errors in or omissions from the information included herein.
- 7. Renesas Electronics products are classified according to the following three quality grades: "Standard", "High Quality", and "Specific". The recommended applications for each Renesas Electronics product depends on the product's quality grade, as indicated below. You must check the quality grade of each Renesas Electronics product before using it in a particular application. You may not use any Renesas Electronics product for any application categorized as "Specific" without the prior written consent of Renesas Electronics. Further, you may not use any Renesas Electronics. Renesas Electronics shall not be in any way liable for any damages or losses incurred by you or third parties arising from the use of any Renesas Electronics product for an application categorized as "Specific" or for which the product is not intended where you have failed to obtain the prior written consent of Renesas Electronics. The quality grade of each Renesas Electronics product is "Standard" unless otherwise expressly specified in a Renesas Electronics data sheets or data books, etc.
 - "Standard": Computers; office equipment; communications equipment; test and measurement equipment; audio and visual equipment; home electronic appliances; machine tools; personal electronic equipment; and industrial robots.
 - "High Quality": Transportation equipment (automobiles, trains, ships, etc.); traffic control systems; anti-disaster systems; anticrime systems; safety equipment; and medical equipment not specifically designed for life support.
 - "Specific": Aircraft; aerospace equipment; submersible repeaters; nuclear reactor control systems; medical equipment or systems for life support (e.g. artificial life support devices or systems), surgical implantations, or healthcare intervention (e.g. excision, etc.), and any other applications or purposes that pose a direct threat to human life.
- 8. You should use the Renesas Electronics products described in this document within the range specified by Renesas Electronics, especially with respect to the maximum rating, operating supply voltage range, movement power voltage range, heat radiation characteristics, installation and other product characteristics. Renesas Electronics shall have no liability for malfunctions or damages arising out of the use of Renesas Electronics products beyond such specified ranges.
- 9. Although Renesas Electronics endeavors to improve the quality and reliability of its products, semiconductor products have specific characteristics such as the occurrence of failure at a certain rate and malfunctions under certain use conditions. Further, Renesas Electronics products are not subject to radiation resistance design. Please be sure to implement safety measures to guard them against the possibility of physical injury, and injury or damage caused by fire in the event of the failure of a Renesas Electronics product, such as safety design for hardware and software including but not limited to redundancy, fire control and malfunction prevention, appropriate treatment for aging degradation or any other appropriate measures. Because the evaluation of microcomputer software alone is very difficult, please evaluate the safety of the final products or system manufactured by you.
- 10. Please contact a Renesas Electronics sales office for details as to environmental matters such as the environmental compatibility of each Renesas Electronics product. Please use Renesas Electronics products in compliance with all applicable laws and regulations that regulate the inclusion or use of controlled substances, including without limitation, the EU RoHS Directive. Renesas Electronics assumes no liability for damages or losses occurring as a result of your noncompliance with applicable laws and regulations.
- 11. This document may not be reproduced or duplicated, in any form, in whole or in part, without prior written consent of Renesas Electronics.
- 12. Please contact a Renesas Electronics sales office if you have any questions regarding the information contained in this document or Renesas Electronics products, or if you have any other inquiries.
- (Note 1) "Renesas Electronics" as used in this document means Renesas Electronics Corporation and also includes its majorityowned subsidiaries.
- (Note 2) "Renesas Electronics product(s)" means any product developed or manufactured by or for Renesas Electronics.

RENESAS

H7N1002LD, H7N1002LS, H7N1002LM


Silicon N Channel MOS FET High Speed Power Switching

REJ03G1131-0800 Rev.8.00 Nov 13, 2009

Features

- Low on-resistance
- $R_{DS(on)} = 8 \text{ m}\Omega \text{ typ.}$
- Low drive current
- Available for 4.5 V gate drive

Outline



Absolute Maximum Ratings

			$(Ta = 25^{\circ}C)$
Item	Symbol	Value	Unit
Drain to source voltage	V _{DSS}	100	V
Gate to source voltage	V _{GSS}	±20	V
Drain current	ID	75	A
Drain peak current	I _{D (pulse)} Note 1	300	A
Body to drain diode reverse drain current	I _{DR}	75	A
Avalanche current	I _{AP} Note 3	50	A
Avalanche energy	E _{AR} Note 3	166	mJ
Channel dissipation	Pch Note 2	100	W
Channel temperature	Tch	150	٥C
Storage temperature	Tstg	-55 to +150	٥°

Notes: 1. $PW \le 10 \ \mu s$, duty cycle $\le 1\%$

2. Value at Tc = 25° C


3. Value at Tch = 25°C, Rg \geq 50 Ω


Electrical Characteristics


						$(Ta = 25^{\circ}C)$
Item	Symbol	Min	Тур	Max	Unit	Test Conditions
Drain to source breakdown voltage	V (BR) DSS	100	—	—	V	$I_D = 10 \text{ mA}, V_{GS} = 0$
Gate to source breakdown voltage	V (BR) GSS	±20	—		V	$I_G = \pm 100 \ \mu A, \ V_{DS} = 0$
Gate to source leak current	I _{GSS}	—	—	±10	μA	$V_{GS}=\pm 16~V,~V_{DS}=0$
Zero gate voltage drain current	I _{DSS}	—	—	10	μA	$V_{DS} = 100 V, V_{GS} = 0$
Gate to source cutoff voltage	$V_{GS \ (off)}$	1.5	—	2.5	V	$I_D = 1 \text{ mA}, V_{DS} = 10 \text{ V}^{Note 4}$
Static drain to source on state	R _{DS (on)}	—	8	10	mΩ	$I_D = 37.5 \text{ A}, V_{GS} = 10 \text{ V}^{Note 4}$
resistance		—	10	15	mΩ	$I_D = 37.5 \text{ A}, V_{GS} = 4.5 \text{ V}^{Note 4}$
Forward transfer admittance	y _{fs}	57	95	—	S	$I_D = 37.5 \text{ A}, V_{DS} = 10 \text{ V}^{Note 4}$
Input capacitance	Ciss	—	9700	_	pF	V _{DS} = 10 V
Output capacitance	Coss	—	740	_	pF	$V_{GS} = 0$
Reverse transfer capacitance	Crss	—	330	—	pF	f = 1 MHz
Total gate charge	Qg	—	155	—	nC	V _{DD} = 50 V
Gate to source charge	Qgs	—	35	—	nC	V _{GS} = 10 V
Gate to drain charge	Qgd	—	33	—	nC	I _D = 75 A
Turn-on delay time	t _{d (on)}	—	43	—	ns	$V_{GS} = 10 \text{ V}, \text{ I}_{D} = 37.5 \text{ A}$
Rise time	tr	—	245	—	ns	$R_L = 0.8 \Omega$
Turn-off delay time	t _{d (off)}	—	130	—	ns	Rg = 4.7 Ω
Fall time	t _f	—	25	—	ns	
Body to drain diode forward voltage	V_{DF}	—	0.93	—	V	$I_F = 75 \text{ A}, V_{GS} = 0$
Body to drain diode reverse recovery	t _{rr}	—	70	—	ns	$I_F = 75 \text{ A}, V_{GS} = 0$
time						$di_F/dt = 100 \text{ A}/\mu \text{s}$


Note: 4. Pulse test

Main Characteristics












Package Dimensions





H7N1002LD, H7N1002LS, H7N1002LM



Ordering Information

Part Name	Quantity	Shipping Container	
H7N1002LD-E	500 pcs	Box (Conductive Sack)	
H7N1002LSTL-E	1000 pcs	Taping	
H7N1002LMTL-E	1000 pcs	Taping	

RenesasTechnology Corp. sales Strategic Planning Div. Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan

- Benesas lechnology Corp. Sales Strategic Planning Div. Nippon Bldg., 2-6-2, Ohte-machi, Chiyoda-ku, Tokyo 100-0004, Japan
 Pines
 This document is provided for reference purposes only so that Renesas customers may select the appropriate Renesas products for their use. Renesas neither makes warranties or representations with respect to the accuracy or completeness of the information in this document.
 This document is provided for reference purposes only so that Renesas customers may select the appropriate Renesas products for the intersect on the information in this document.
 The document is provided for reference purposes only so that Renesas customers may select the appropriate Renesas products for the tendology described in this document.
 The order data. diagrams, charts, programs, algorithms, and application circuit examples, is current as of the date their document with a pay with use. When exporting the products or the tendology described herein, you should follow the applicable export control laws and regulations, and proceedures required by such laws and regulations.
 All information included in this document, but as product data, diagrams, charts, programs, algorithms, and application circuit examples, is current as of the date this document, but Renesas assumes no liability whattowere for any damages incurred as a set of eason devine of the interse of the interse of the date their document, included in this document, but Renesas assumes no liability whattowere for any damages incurred as a disclosed by Renesas sub at that disclosed through dure their document.
 When using or otherwise relevance on their document, and their document, but Renesas as and their document and their document.
 When using or otherwise relevance on the date date disclosed through application, in the document.
 When using or otherwise relevance on their document.
 When using or otherwise relevance on their document and this document.



RENESAS SALES OFFICES

Refer to "http://www.renesas.com/en/network" for the latest and detailed information.

Renesas Technology America, Inc.

450 Holger Way, San Jose, CA 95134-1368, U.S.A Tel: <1> (408) 382-7500, Fax: <1> (408) 382-7501

Renesas Technology Europe Limited Dukes Meadow, Millboard Road, Bourne End, Buckinghamshire, SL8 5FH, U.K. Tel: <44> (1628) 585-100, Fax: <44> (1628) 585-900

Renesas Technology (Shanghai) Co., Ltd. Unit 204, 205, AZIACenter, No.1233 Lujiazui Ring Rd, Pudong District, Shanghai, China 200120 Tel: <86> (21) 5877-1818, Fax: <86> (21) 6887-7858/7898

Renesas Technology Hong Kong Ltd. 7th Floor, North Tower, World Finance Centre, Harbour City, Canton Road, Tsimshatsui, Kowloon, Hong Kong Tel: <852> 2265-6688, Fax: <852> 2377-3473

Renesas Technology Taiwan Co., Ltd. 10th Floor, No.99, Fushing North Road, Taipei, Taiwan Tel: <886> (2) 2715-2888, Fax: <886> (2) 3518-3399

Renesas Technology Singapore Pte. Ltd.

1 Harbour Front Avenue, #06-10, Keppel Bay Tower, Singapore 098632 Tel: <65> 6213-0200, Fax: <65> 6278-8001

Renesas Technology Korea Co., Ltd. Kukje Center Bldg. 18th Fl., 191, 2-ka, Hangang-ro, Yongsan-ku, Seoul 140-702, Korea Tel: <82> (2) 796-3115, Fax: <82> (2) 796-2145

Renesas Technology Malaysia Sdn. Bhd Unit 906, Block B, Menara Amcorp, Amcorp Trade Centre, No.18, Jln Persiaran Barat, 46050 Petaling Jaya, Selangor Darul Ehsan, Malaysia Tel: <603> 7955-9390, Fax: <603> 7955-9510

http://www.renesas.com