

Sleeve housing - HC-B 32-TFQ-80/O1PG36S X - 1646036

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://download.phoenixcontact.com>)

HEAVYCON B32 sleeve housing, for double locking latch, height: 80 mm, with 1 x Pg29 gland, lateral cable outlet

Key commercial data

| | |
|--------------------------------------|-----------|
| Packing unit | 1 PCE |
| Weight per Piece (excluding packing) | 460.8 GRM |
| Custom tariff number | 85389099 |
| Country of origin | Germany |

Technical data

Dimensions

| | |
|--------|-------|
| Height | 80 mm |
| Width | 79 mm |
| Length | 94 mm |

Ambient conditions

| | |
|--------------------------------------|-------------------|
| Degree of protection of housing (IP) | IP65 |
| Ambient temperature (operation) | -40 °C ... 125 °C |

General

| | |
|------------------------------|--------------------------------------|
| Note | For contact inserts HC-B32, DD144, M |
| Design | B32 |
| Housing type | Sleeve housings |
| Locking type | For double locking latch |
| Cable exit | Lateral |
| Screw connection | None |
| Type of the screw connection | 1x Pg36 |
| Housing material | Aluminum die-cast |
| Housing surface material | Powder-coated, gray |

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 4.0 | 27140816 |
| eCl@ss 4.1 | 27140816 |
| eCl@ss 5.0 | 27143424 |
| eCl@ss 5.1 | 27143424 |

Sleeve housing - HC-B 32-TFQ-80/O1PG36S X - 1646036

Classifications

eCl@ss

| | |
|------------|----------|
| eCl@ss 6.0 | 27143424 |
| eCl@ss 7.0 | 27440209 |

ETIM

| | |
|----------|----------|
| ETIM 3.0 | EC000437 |
| ETIM 4.0 | EC000437 |
| ETIM 5.0 | EC000437 |

UNSPSC

| | |
|---------------|----------|
| UNSPSC 6.01 | 31261502 |
| UNSPSC 7.0901 | 31261502 |
| UNSPSC 11 | 31261502 |
| UNSPSC 12.01 | 31261502 |
| UNSPSC 13.2 | 31261502 |