



NOTES:

- 1) MATERIAL: SEE TABLE
- 2) FINISHES: SEE TABLE
- 3) WRAP LABEL IS MARKED WITH P/N, DATE CODE VOLTAGE & AMPERAGE
- 4) MATES WITH: MINI CHANGE 4 POLE RECEPTACLE, ALT-KEY
- 5) ELECTRICAL DATA:  
 14AWG UL TYPE: TC-ER  
 POLES: 4  
 MAX VOLTAGE: 600V  
 MAX CURRENT: 15A  
 PROTECTION IP67  
 TEMPERATURE RANGE: -20°C TO 90°C
- 6) PACKAGING:  
 CABLE ASSEMBLIES ARE BAGGED SEPERATLY IN POLY BAGS WITH BAR CODE LABEL ATTACHED TO OUTSIDE OF BAG.

BLACK #1	P1
BLACK #2	1
BLACK #3	2
GREEN/YELLOW	3
	4

WIRING DIAGRAM

PART NUMBER LEGEND

104106K21MXXX Ⓐ

MC 4P SE, MALE, ALT KEY  
 CABLE TYPE: 14 AWG TC ER  
 FINISHED LENGTH:  
 M001= .1M  
 M010= 1.0M  
 M100= 10.0M

7	1	WARNING LABEL	VINYL	ORANGE/BLACK
6	1	WRAP LABEL	VINYL	BLACK/YELLOW
5	1	OVERMOLD	PVC	BLACK
4	1	MALE COUPLING NUT	ZINC ALLOY	BLACK
3	4	PIN CONTACT	CU ALLOY	GOLD PLATE
2	1	MALE INSERT	PVC	BLACK
1	SEE LEGEND	CABLE	TPE	BLACK
ITEM	QTY	DESCRIPTION	MATERIAL	FINISH

REMOVED 'G' FROM P/N	2015/11/16
EC NO: IPG2016-0734	2015/12/09
DRWINRSTONE	2016/02/29
CHKD:KJOWIK	
APPR:BMOODMAN	
DESCRIPTION	
REV	
A1	

QUALITY SYMBOLS	GENERAL TOLERANCES (UNLESS SPECIFIED)
▽=0	mm INCH
▽=0	4 PLACES ± --- ± ---
	3 PLACES ± --- ± .005
	2 PLACES ± 0.13 ± .010
	1 PLACE ± 0.25 ± .020
	0 PLACE ± --- ± ---
	ANGULAR ±1/2°
	DRAFT WHERE APPLICABLE MUST REMAIN WITHIN DIMENSIONS

DIMENSION STYLE	SCALE	DESIGN UNITS
IN/MM	1:1	INCH
DRAWN BY	DATE	TITLE
BARDEN	2014/12/03	MINI-CHANGE ASSEMBLY
CHECKED BY	DATE	4P M/MP ST ALT KEY
RSTONE	2014/12/5	#14AWG CABLE
APPROVED BY	DATE	<b>molex</b>
JFMURPHY	2014/12/08	DOCUMENT NO.
MATERIAL NO.	---	SD-130061-027

THIRD ANGLE PROJECTION	SHEET NO.
	1 OF 1
THIS DRAWING CONTAINS INFORMATION THAT IS PROPRIETARY TO MOLEX INCORPORATED AND SHOULD NOT BE USED WITHOUT WRITTEN PERMISSION	