



VE-204TS

VE-324TS



► **Features**

- High contrast LCD screen.
- Large stainless steel pan.
- Capacity tracker
- Leveling feet: Two back feet
- RS 232 interface.
- 3 Door anti-static draft shield.
- Multiple weighing units.

► **Standard Functions**

- |                          |                     |                                      |
|--------------------------|---------------------|--------------------------------------|
| • Weighing               | • Percent weighing  | • Hold function                      |
| • Density weighing       | • Computer function | • Dynamic weighing                   |
| • High low limit alarm   | • Counting function | • Gross / net / tare weight weighing |
| • Accumulation function" |                     |                                      |

► **Accessories Included**

- |                            |                |                                |
|----------------------------|----------------|--------------------------------|
| • Calibration weight F1100 | • RS232 Cable. | • Hook for suspending weighing |
| • Glove                    | • USB Adapter  | • Dust cover                   |

► **TECHNICAL DATA**

Model	VE-204TS	VE-324TS
Capacity	220 g / 320 g	320 g
Readability	0.1 mg / 1 mg	0.1 mg / 1mg
Repeatability	±0.1 mg / ±1 mg	±0.1 mg / ±1mg
Linearity	±0.2 mg / ±2 mg	±0.2 mg / ±2mg
Weighing mechanism	Monoblock	
Weighing Units	g, mg, ct, oz, ozt, dwt, GN, lb, N, dr, tIT, tIS, tIH, T(Tola), ms (Mesghal) , bat, /lb (Parts per pound) ,mom, kg, totally 19units selectable and 2 units customizable	
Calibration	Internal CAL	
Pan Size	Ø 90 mm / Ø 3.5"	
Stabilization Time	1.5 ~ 4 seconds	
Interface	RS-232 and USB.	
Display size	5" Touchscreen display	
Housing	Metal base and ABS plastic	
Operating Environment	15° to 23°C / 59° to 75°F / Humidity 20% - 80%	
Overall Dimensions	345 X 223 X 331mm / 653" x 433" x 628"	
Underhook mechanism	Hook included.	
Power Supply	110/240V, 50/60 AC Adapter	
Net Weight	5.2 kg / 11.5 lb	
Warranty	2 years	