



- NOTES:
1. RECOMMENDED DIAMETER FOR THROUGH HOLE (SCREW/NUT COMBINATION) HARDWARE MOUNTING METHOD. OTHER METHODS WILL REQUIRE HOLES WITH DIFFERENT DIMENSIONS AND PARAMETERS.
 2. HOUSING TOLERANCE +/- .25 UDS.

THIS DOCUMENT AND ITS CONTENTS ARE THE PROPRIETARY, CONFIDENTIAL PROPERTY OF INTERPOWER CORPORATION. NO USE OR COPIES MAY BE MADE WITHOUT WRITTEN PERMISSION FROM INTERPOWER.

DIMENSIONS: MM

TITLE SHEET F - SCREW MOUNT
QUICK DISCONNECT CONTACTS

DRAFT BY: BEM DATE: 6-5-12

ASSY NUMBER: 83030600

DRAFTING APPROVAL: SRK DATE: 6-5-12

MATERIAL:

DO NOT SCALE

INTERPOWER
CORPORATION

SHEET 1 OF 1

| REV | CHANGE DESCRIPTION | DATE | BY |
|-----|------------------------------|---------|-----|
| 3 | Added enhanced holding tabs. | 4-16-21 | DDF |
| 2 | 1) ADDED NOTE 2. | 8-6-12 | BEM |
| 1 | INITIAL RELEASE | 6-5-12 | BEM |