



3 Type

- A Without nylon locking element
- N With nylon locking element

Inch table

Dimensions in: inches - millimeters

d ₁ Thread	d ₂	Length l	w Compression	Color	Spring load ≈	
					Initial	End
10 x 32*	0.0937 2.4	0.513 13.0	0.025 0.6	ZINC	0.50 lbf 2.22 N	1.50 lbf 6.67 N
10 x 32*	0.0937 2.4	0.513 13.0	0.025 0.6	BLACK	1.50 lbf 6.67 N	3.00 lbf 13.34 N
10 x 32*	0.0937 2.4	0.513 13.0	0.025 0.6	GOLD	2.00 lbf 8.89 N	5.00 lbf 22.24 N
1/4 x 20*	0.1250 3.2	0.531 13.5	0.035 0.9	ZINC	2.00 lbf 8.89 N	4.00 lbf 17.79 N
1/4 x 20*	0.1250 3.2	0.531 13.5	0.035 0.9	BLACK	3.00 lbf 13.34 N	7.00 lbf 31.13 N
1/4 x 20*	0.1250 3.2	0.531 13.5	0.035 0.9	GOLD	4.00 lbf 17.79 N	12.00 lbf 53.37 N
5/16 x 18	0.1560 4.0	0.578 14.7	0.040 1.0	ZINC	2.00 lbf 8.89 N	4.50 lbf 20.01 N
5/16 x 18	0.1560 4.0	0.578 14.7	0.040 1.0	BLACK	4.00 lbf 17.79 N	9.00 lbf 40.03 N
5/16 x 18	0.1560 4.0	0.578 14.7	0.040 1.0	GOLD	6.00 lbf 26.68 N	17.00 lbf 75.61 N
3/8 x 16	0.1875 4.8	0.625 15.9	0.048 1.2	ZINC	2.50 lbf 11.12 N	5.00 lbf 22.24 N
3/8 x 16	0.1875 4.8	0.625 15.9	0.048 1.2	BLACK	5.00 lbf 22.24 N	10.00 lbf 44.48 N
3/8 x 16	0.1875 4.8	0.625 15.9	0.048 1.2	GOLD	6.00 lbf 26.68 N	21.00 lbf 93.41 N
1/2 x 13	0.2813 7.1	0.750 19.1	0.072 1.8	ZINC	3.00 lbf 13.34 N	6.00 lbf 26.68 N
1/2 x 13	0.2813 7.1	0.750 19.1	0.072 1.8	BLACK	6.00 lbf 26.68 N	12.00 lbf 53.37 N
1/2 x 13	0.2813 7.1	0.750 19.1	0.072 1.8	GOLD	6.00 lbf 26.68 N	30.00 lbf 133.44 N
5/8 x 11	0.3750 9.5	0.984 25.0	0.096 2.4	ZINC	4.50 lbf 20.01 N	9.00 lbf 40.03 N
5/8 x 11	0.3750 9.5	0.984 25.0	0.096 2.4	BLACK	9.00 lbf 40.03 N	18.00 lbf 80.06 N
5/8 x 11	0.3750 9.5	0.984 25.0	0.096 2.4	GOLD	7.00 lbf 31.13 N	50.00 lbf 222.41 N

* These sizes come with a nylon patch instead of a nylon locking element

Specification

- Steel housing / spring
- Stainless steel ball AISI 440C
- Color / end spring load
 - **Zinc** plated housing: light
 - **Black** oxide housing: standard
 - **Gold** chromate housing: heavy
- *Stainless Steel Characteristics* → page 2143
- **RoHS compliant**

Information

BP ball plungers are compact units ideally suited for many locating or positioning applications in dies, special tooling, automatic feed devices, etc. where controlled end spring load is required.

The locking element is supplied as either a patch or pellet and is not recommended for use in aluminum applications.

<p>How to order</p> <p>BP-10X32-6.67-A</p>	1	Thread d ₁
	2	End spring load (N)
	3	Type

3.1
3.2
3.3
3.4
3.5
3.6
3.7
3.8
3.9
3.10