## **HellermannTyton**

## **Specification Sheet**

Part Number: TAG96L-789



Laser printable white polyester has a smooth surface, allowing for the highest resolution and print contrast.

The acrylic-based adhesive bonds to a wide variety of substrates and can withstand high temperatures long term.

Lasertags are not affected by the high heat required in a laser printer.

Laser Tag Label, 1.875" x .25", 144 Per Sheet, PET, White, 1000/pkg

Article Number 594-96789

Type TAG96L

Color White (WH)

Quantity Per pack

**Product Description** 

HellermannTyton white polyester labels are ideal for marking small electrical and electronic components, such as EPROMS', Integrated circuits, as well as the circuit board itself. Printed labels can withstand the soldering process and survive flux removal when the board is washed. HellermannTyton's 789 material is designed for use on flat surfaces and can also be used to identify connectors, buttons and just about anything requiring permanent, durable, high temperature and UV resistant marking.

**Short Description** 

Laser Tag Label, 1.875" x .25", 144 Per Sheet, PET, White, 1000/pkg

<b>~</b>		
Global	Part	Nama
Olobai	ı aıı	INGILIC

TAG96L-789-WH

Width W (Imperial)

1.875

Width W (Metric)

47.62

Thickness T (Metric)

64.0

Height H (Imperial)

0.25

Height H (Metric)

6.35

Material

Type 789, Polyester (789)

**Material Shortcut** 

789

Adhesive

Acrylic

Halogen Free

No

UV Resistant (Yes/No)

No

Adhesive Operating Temperature

-40°F to +302°F (-40°C to +150°C)

**Operating Temperature** 

-40°F to +300°F (-40°C to +149°C)

Reach Compliant (Article 33)

Yes

**ROHS Compliant** 

Yes

Package Quantity (Imperial) 1000

Package Quantity (Metric) 1000

Customs Number 3919905060

Labels per Column 36

Labels per Row 4

## About HellermannTyton

HellermannTyton is a global manufacturer of cable management and identification solutions for automotive, solar, electrical, construction, industrial automation, broadband and other OEM markets. The company's integrated approach to product design, sustainability, production, quality assurance and delivery is optimized to benefit local and global customers. HellermannTyton operates in 39 countries, with North American headquarters in Milwaukee, Wisconsin. (www.hellermann.tyton.com).

© 2023 HellermannTyton. All Rights Reserved.

Contact Us RoHS/WEEE Compliance Disclaimer Terms and Conditions