



## **1.GENERAL SPECIFICATIONS:**

'A'

RATING: 10A / 125V AC

CABLE TYPE / SIZE: SVT, # 18 AWG, 3 CONDUCTOR

TEMPERATURE RATING: 60° C MIN.

CONDUCTOR COLORS: BLACK / WHITE / GREEN

CABLE JACKET COLOR: BLACK

OVERALL LENGTH (L):  $1570 \pm 50 \text{ mm} (5 \text{ FT})$ 

CABLE OUTER DIAMETER:  $6.3 \pm 0.1 \text{ mm}$ END 'A' PLUG; NEMA 5-15P

END 'B' SEE TERMINATION TABLE

APPROVALS PLUG: UL, CSA OR cUL APPROVALS CABLE: UL, CSA OR cUL

**CONDUCTOR TERMINATION TABLE:** 

## 2.PACKING:

BULK PACKED, BUNDLES OF 25.

MAXIMUM SHIPPING CARTON WEIGHT IS 30 KG.

## 3.NOTES:

1. CORD, PLUG AND CONNECTOR MUST BE MARKED WITH APPROVAL SYMBOLS OR FILE NUMBER(S).





OR



APPROVED

BS

12/14/00

11/02/04

## 2. CABLE STRANDING IS 41/34.

Wire	Color	ROJ <u>+</u> 5 mm	PARTIALSTRIP	TERMINATION				
NEUTRAL	WHT	90	10	PARTIAL STRIP				
LINE	BLK	90	10	PARTIAL STRIP				
GROUND	GRN	90	-	# 6 RING (SERRATED) TYPE T-6895/ J6176BS-2 OR EQUIVALENT				

	•											
			DASH NO.		PART NO		REV.	DESCRIPTION			NOTES	
				TABULATION BLOCK								
			REV. SHEET	D			DEC .xx	LERAN MALS +/- 0.1 +/005	NCES: ANGULAR +/- 1°	GlobTek, Inc.  www.globtek.com  186 Veterans Dr. No. Tel. 201-784-1000		
Contents of this document are subject to change without prior notice	Foot Note: Globtek Inc. will not be liable for the safety and performance of these power product if unauthorized access and repair occurs. End user should consult the applica- ble UL,CSA or EN Standards for proper installation instruction.	Globek product are not authorized tor use as mission critical components in life support, hazardous environment, nuclear or aircraft applications without prior written composed from the CPO of Globald Inc.	INIT.BY: DMR		DATE: 11/02/04	DATE: 11/02/04	MILLIMET .xx +/- 0 .xxx +/	METERS ANGULAR -/- 0.3 +/- 1°	I W Wigioble Riccini			
			DRAWN, NI		11/02/04		FSCN G, YL		SIZE A		REV. D	
			APRVD: DMR		DATE: 11/02/04		SCALE: NONE		NE	PART NO: 3021445F200T	SHEET 1/1	