

Energy storage - QUINT-BAT/24DC/ 7.2AH - 2866352

Please be informed that the data shown in this PDF Document is generated from our Online Catalog. Please find the complete data in the user's documentation. Our General Terms of Use for Downloads are valid (<http://phoenixcontact.com/download>)



Energy storage device, lead AGM, VRLA technology, 24 V DC, 7.2 Ah. Connection via pin cable lug, 14 mm.



Key Commercial Data

Packing unit	1 STK
Weight per Piece (excluding packing)	7194.6 g
Custom tariff number	85072080
Country of origin	China

Technical data

Dimensions

Width	164 mm
Height	156 mm
Depth	110 mm

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	0 °C ... 40 °C
Ambient temperature (storage/transport)	0 °C ... 40 °C

Input data

Nominal input voltage	24 V DC
-----------------------	---------

Output data

Nominal output voltage	24 V DC
Output current I_{max}	50 A
Connection in parallel	Yes, for increasing the buffer period
Connection in series	No

Energy storage - QUINT-BAT/24DC/ 7.2AH - 2866352

Technical data

Output data

Output fuse	2x 25 A
-------------	---------

General


IQ technology	No
Net weight	6 kg
Memory medium	battery 7.2 Ah
Protection class	III

Standards and Regulations

Shipbuilding approval	Germanischer Lloyd (EMC 2), ABS
-----------------------	---------------------------------

Drawings

Block diagram



Classifications

eCl@ss

eCl@ss 4.0	27040603
eCl@ss 4.1	27040603
eCl@ss 5.0	27040603
eCl@ss 5.1	27040603
eCl@ss 6.0	27040603
eCl@ss 7.0	27049201
eCl@ss 8.0	27050403
eCl@ss 9.0	27050403

ETIM

ETIM 2.0	EC000382
ETIM 3.0	EC000382
ETIM 4.0	EC000357
ETIM 5.0	EC000357

Energy storage - QUINT-BAT/24DC/ 7.2AH - 2866352

Classifications

UNSPSC

UNSPSC 6.01	30211510
UNSPSC 7.0901	39121011
UNSPSC 11	39121011
UNSPSC 12.01	39121011
UNSPSC 13.2	39121011

Approvals

Approvals

Approvals

GL / EAC / EAC / DNV / ABS / ABS

Ex Approvals

Approvals submitted

Approval details

GL

EAC

EAC

DNV

ABS

ABS

Accessories

Accessories

Assembly adapter

Energy storage - QUINT-BAT/24DC/ 7.2AH - 2866352

Accessories

Assembly adapters - QUINT-ADAPTER/4 - 2866857

Assembly adapter for QUINT-BAT/24DC... on 35mm rail



Fuse

Fuse - SI FORM C 25 A DIN 72581 - 0913757



Flat-type plug-in fuse, type C, color code: white, nominal current: 25 A
