2 METERS LENGTH



Connector A 132119 SMA Jack Straight Bulkhead - Rear Mount Brass Gold + Heatshrink 50 Ohm RG-316 Continuity/Hi-Pot Connector B 034-5067 HD-BNC Plug Straight Brass Nickel IP67 + Heatshrink

Assembly & Label Notes

Assembly label to be placed ~ 2" from end of connector A and/ or heat shrink Assembly shall be built with SN96.5 LEAD FREE solder. See Routing Notes for additional assembly & testing instructions.

		Connector A		Cable			Connector B		
D Ty G B C P P In M B B B IP C M	escription: ype: eender: ody Type: ontact Type: olarity: npedance: lounting: ody Material: ody Finish: P Rating: ontact Material: ontact Finish: lax. Freq.:	SMA Jack pe: Straight Type: Solder Standard tee: 50 Ohm g: Bulkhead - Rear Mount terial: Brass hish: Gold g: None Material: Beryllium Copper Finish: Gold q: 12.4 GHz		Part #: Description: Dielectric: Shielding: Diameter: Impedance: Sheathing: Testing: Length:	RG-316 - ST 0.102 ST Braid 0.102 50 Ohm None Continuity Hi-Pot 2 Meters	Part #: Description: Type: Gender: Body Type: Contact Type: Polarity: Impedance: Mounting: Body Material: Body Finish: IP Rating: Contact Material: Contact Finish: Max. Freq.: Booting: Clocking:	HD-BNC Plug Straight Crimp Standard 50 Ohm Cable Brass Nickel IP67 Phospor Bronze Gold 6 GHz	HD-BNC PLUG RG316 IP67 500 HD-BNC Plug Straight Crimp Standard 50 Ohm Cable Brass Nickel IP67 Phospor Bronze Gold 6 GHz HD-BNC Plug RG316 IP67 500	
Amphenol CUSTOM CABLE CONTROLLED DOCUMENT - DO NOT COPY			THIS DRAWING MAY CONTAIN PATENTED OR PROPRIETARY INFORMATION AND MUST NOT BE USED FOR ANY PURPOSE DETRIMENTAL TO CUSTOM CABLE INC. IT MAY NOT BE REPRODUCED OR TRANSCRIBED IN ANY FORM WITHOUT THE WRITTER CONSENT OF CUSTOM CABLE INC. ACCEPTANCE OF THIS DRAWING ESTABLISHES AND AGREEMENT OF THE FOREGOING.		BLE ED F NG Part No:	SMA-ST-JK/HDBNC-ST-PL G316 2M		UNLESS SPECIFIED TOLERANCE: 0-18 inches +/- 1/2" over 18" +/- 2% ASSEMBLY: CENTER LABEL IF LENGTH IS LESS THAN 12 INCHES	



RoHS 2015/863 Compliance Statement

According to the manufacture of all the component parts contained in this assembly, this product has been determined to be RoHS Compliant with RoHS Directive 2011/65/EU and as amended by Directive 2015/863, and without material exceptions (RoHS3 Complaint).

For the individual component RoHS certificates used in this assembly, please contact Amphenol Custom Cable.

The RoHS Compliance of any product so designated is based upon evidence from the producer (manufacturers') that the component parts comply with the RoHS Directive. Amphenol Custom Cable has taken all reasonable steps to confirm that the OEM (Manufacturer) of the components used in this assembly have provided evidence regarding the absence of the restricted substances to support the manufacturer's claim of compliance.

To the best of our knowledge and with due diligence, we certify that the product listed herein complies with the RoHS requirements.

Date: 10/3/2023

Part Number: Q-2W05H0005002M

Manufacturer: Amphenol Custom Cable

Description: SMA-ST-JK/HDBNC-ST-PL G316 2M

This information is valid as of the date indicated for the item (part number) listed.

Director of Quality Assurance

Janice Frank