



## VRLA Rechargeable Battery

# BP3.6-12



### FEATURES

- Maintenance free(no water topping-up required).
- No free acid(Non-spillable battery).
- Low self-discharge rate, lower than 3% capacity loss per month.
- Can be used in any orientation(excluding used inverted).
- Absorbent Glass Mat technology for efficient gas recombination.

### APPLICATION

- UPS
- Electronic Toy-Cars
- Fans
- Emergency Lights
- Rechargeable Flashlights



### SPECIFICATIONS

Nominal Voltage	12 V
Nominal Capacity	3.6Ah @ 20 hour rate F.V.(1.75V/cell)
Approx. Weight	1320g(2.91lbs.)
Terminals	T1 (Faston Tab 187) T2 is optional
Internal Resistance	≤50m Ω (Fully Charged )
Max. Discharge Current	54 A (5 sec.)
Max. Charge Current	1.08 A
Operating Temperature Range	Charge : 0°C~40°C(32°F~104°F) Discharge : -20°C~50°C(-4°F~122°F) Storage. : -20°C~40°C(-4°F~104°F)
Container Material	Standard: ABS( UL 94-HB) BP3.6-12 Optional: Flame Retardant ABS(UL 94-V0) BP3.6-12FR

- IEC 61056-1
- JIS C 8702-1
- GB/T 19639.1

DIMENSION(mm/inch)	OUTER DIMENSIONS	TERMINAL TYPE
<p>■ <b>Length</b> 134±1.5 (5.28±0.06)</p> <p>■ <b>Width</b> 67±1.5 (2.64±0.06)</p> <p>■ <b>Container Height</b> 60±1.5 (2.36±0.06)</p> <p>■ <b>Total Height</b> 66±2.0 (2.60±0.08)</p>		<p>• Terminal T1</p> <p>• Terminal T2</p>

### Constant power discharge characteristics at 25 °C/77 °F Unit: W

F.V. (V/cell) \ Discharge Time	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	130.2	95.8	76.8	45.69	26.20	10.49	7.235	4.043	2.128
1.75V	150.7	103.8	80.3	47.42	26.99	10.70	7.344	4.104	2.160
1.70V	160.1	107.5	82.8	48.51	27.47	10.80	7.384	4.124	2.174
1.65V	167.3	110.1	84.7	49.19	27.80	10.88	7.410	4.137	2.174
1.60V	172.8	112.3	86.4	49.68	28.08	10.94	7.432	4.137	2.174

### Constant current discharge characteristics at 25 °C/77 °F Unit: A

F.V. (V/cell) \ Discharge Time	5 Min	10 Min	15 Min	30 Min	1 Hr	3 Hr	5 Hr	10 Hr	20 Hr
1.80V	11.73	8.43	6.68	3.87	2.202	0.874	0.603	0.337	0.177
1.75V	13.82	9.14	6.98	4.02	2.268	0.892	0.612	0.342	0.180
1.70V	14.68	9.47	7.20	4.11	2.309	0.900	0.615	0.344	0.181
1.65V	15.34	9.69	7.37	4.17	2.336	0.906	0.617	0.345	0.181
1.60V	15.85	9.89	7.51	4.21	2.360	0.912	0.619	0.345	0.181

All data and artworks shall be changed without prior notice, BB reserves the right to explain and update the information contained hereinto.