

SIMATIC IPC277E (Nanopanel PC); 9" Touch TFT; 2x 10/100/1000 Mbps Ethernet RJ45; 1x display port graphic; 1x USB 3.0; 2x USB 2.0; 1x serial (COM 1); CFast slot; 24 V DC power supply Celeron N2930 (4C/4T) 8 GB with NVRAM WIN Embedded Standard 7E SP1, English; 64 bit 256 GB Eco SSD; CPU 1507S/WinCC RT Advanced V16 Update 1, 2048 PT;

General information	
Product type designation	IPC277E
Display	
Design of display	9" TFT touch
Screen diagonal	9 in
Resolution (pixels)	
• Horizontal image resolution	800 pixel
• Vertical image resolution	480 pixel
Backlighting	
• MTBF backlighting (at 25 °C)	80 000 h
Control elements	
Touch operation	
• Design as touch screen	Yes; analog, resistive
Installation type/mounting	
central design	Yes
Mounting in portrait format possible	Yes
Power loss	
In full configuration	29 W
Dimensions	
Width of the housing front	274 mm
Height of housing front	190 mm
Mounting cutout, width	251 mm
Mounting cutout, height	166 mm
Overall depth	77 mm
Weights	
Weight, approx.	1.95 kg

**last modified:** 1/31/2021 