



Product: [36102](#)

Lead Wire, #2 Str TC, CSPE Ins, 5000V

Request Sample

### Product Description

Low Temp Rubber Lead Wire, 2AWG (163x24) Tinned Copper, CSPE Insulation, 5000V

### Technical Specifications

#### Product Overview

Suitable Applications:	high voltage applications, Class 130(B) motor lead systems, internal wiring of appliances, oil resistance applications
------------------------	--

#### Construction Details

##### Conductor

Element	No. of Elements	Size	Stranding	Material
Conductor(s)	1	2	163x24	TC - Tinned Copper

##### Insulation

Material	Nom. Thickness	Nom. Insulation Diameter
CSPE - Chlorosulphonated Polyethylene	0.162 in (4.11 mm)	0.643 in (16.3 mm)
Overall Cable Diameter (Nominal):	0.643 in (16.3 mm)	

#### Electrical Characteristics

##### Voltage

Voltage Rating
5000 V RMS

#### Mechanical Characteristics

##### Bend Radius

Stationary Min.	Installation Min.
2.58 in (65.5 mm)	2.58 in (65.5 mm)
Max. Pull Tension:	825 lbs (374 kg)
Bulk Cable Weight:	368 lbs/1000ft

#### Standards and Compliance

Sustainability:	CA Prop 65
European Directive Compliance:	EU Directive 2015/863/EU (RoHS 2 amendment), EU Directive 2011/65/EU (RoHS 2), EU Directive 2012/19/EU (WEEE)
APAC Compliance:	China RoHS II (GB/T 26572-2011)

#### Product Notes

Notes:	Separator material over conductor.
--------	------------------------------------

#### History

Update and Revision:	Revision Number: 0.447 Revision Date: 01-20-2023
----------------------	--

#### Part Numbers

**Variants**

Item #	Color	Putup Type	Length	UPC	Footnote
36102 010500	Black	Reel	500 ft	612825145424	C F

© 2023 Belden, Inc

All Rights Reserved.

Although Belden makes every reasonable effort to ensure their accuracy at the time of this publication, information and specifications described here in are subject to error or omission and to change without notice, and the listing of such information and specifications does not ensure product availability.

Belden provides the information and specifications herein on an "ASIS" basis, with no representations or warranties, whether express, statutory or implied. In no event will Belden be liable for any damages (including consequential, indirect, incidental, special, punitive, or exemplary damages) whatsoever, even if Belden has been advised of the possibility of such damages, whether in an action under contract, negligence or any other theory, arising out of or in connection with the use, or inability to use, the information or specifications described herein.

All sales of Belden products are subject to Belden's standard terms and conditions of sale.

Belden believes this product to be in compliance with all applicable environmental programs as listed in the data sheet. The information provided is correct to the best of Belden's knowledge, information and belief at the date of its publication. This information is designed only as a general guide for the safe handling, storage, and any other operation of the product itself or the one that it becomes a part of. The Product Disclosure is not to be considered a warranty or quality specification. Regulatory information is for guidance purposes only. Product users are responsible for determining the applicability of legislation and regulations based on their individual usage of the product.