



SG901-1071

SG901-1071 Miniature Wi-Fi Radio

Overview

The SG901-1071 WiFi module is optimized to simplify successful integration into systems requiring the latest performance with small size. This module is a highly integrated single chip based 802.11b/g/n WLAN radio for embedded, low-power and extremely small form factor mobile applications. The product conforms to the IEEE 802.11B, G, and N protocols operating in the 2.45GHz ISM frequency band supporting 802.11n modulations up to 72.2Mbps, all 802.11g OFDM modulations, and all mandatory 802.11b modulations.


The SG901-1071 is a fully integrated wireless radio including RF Synthesizer/VCO, high-speed data converters, digital baseband processor, onboard MAC and PHY processors, Power Management, Power Amplifier, and LNA.

An on-board EEPROM stores calibration data for alignment-free integration. No customer calibration required.

Bluetooth integration features of the radio are made available.

An on-board crystal and filter simplify system integration. The addition of 1.8V, 3.3V, and VIO supplies, Antenna, and host communication, provides a complete WiFi solution. For maximum flexibility, the SG901-1071 can be optionally supplied without internal oscillator and accept a wide range of external reference clock frequencies.

Host control is provided by either an SDIO or SPI interface.



Features

- Very Small Footprint (12.0 x 9.5 x1.7mm)
- Factory Calibrated
- RoHS Compliant
- Fully Integrated 802.11 System Solution
- Ultra Low Current Consumption, 2.5 m A DITM = 1
- Fully Compliant with the IEEE 802.11B,G, and N WLAN Standards
- Support for 802.11n Modulations up to 72.2Mbps, and all 802.11g and Mandatory 802.11b Modulations
- Intelligent Power Control, Including 802.11 Power Save Mode
- Supports SPI Interface and SDIO Interface
- Factory Support for Linux 2.6/Android, Windows CE
- Source Code Available for porting to RTOS or Custom OS
- Hardware driver is provided under GPL
- Flexible I/O Voltage
- Contact Factory for FCC compliant applications

Applications

- Hand-held Devices
- Embedded Systems
- Portable Systems
- Point of Sale terminals
- Personal Digital Assistants (PDA)
- Cameras
- Cable Replacement

Ordering Information

| Packaging | Temp Range | Part Number |
|---------------|------------|-------------------|
| Tape and Reel | Extended | SG901-1071-ET-TR |
| Bulk | Extended | SG901-1071-ET-BLK |
| Tape and Reel | Commercial | SG901-1071-CT-TR |
| Bulk | Commercial | SG901-1071-CT-BLK |


Evaluation Kit Available

This EVK supports embedded software development.

EVK for 1071

SG923-0007

Block Diagram





SG901-1071

General Electrical Specifications

| Parameter | Test Condition / Comment | Min. | Typ. | Max. | Units |
|---|-------------------------------------|---|-----------|----------|-------|
| Absolute Maximum Ratings | | | | | |
| 3.0V Supply | | -0.3 | | 3.6 | V |
| VLDO Supply | | -0.3 | | 2.5 | V |
| Operating Conditions and Input Power Specifications | | | | | |
| Operating Temperature Range | ET Version (Extended Temperature) | -30 | | 85 | °C |
| | CT Version (Commercial Temperature) | 0 | | 70 | °C |
| 3.3V Supply | Input Supply Voltage | 3.3V Supply input | 2.7 | 3.3 | 3.6 |
| | Standby Mode Current | 32.768kHz Mode | | 270 | uA |
| | Power Save Mode Current | DTIM = 1 | | 2.5 | mA |
| | Peak TX Current | | | 270 | mA |
| | Peak RX Current | Processing Beacons | | 82 | mA |
| | Peak RX Current | Processing OFDM Packets | | 135 | mA |
| Power Save Mode Settling Times | Wake up Time | From 32.768KHz Mode | | 5 | ms |
| | Ramp up | To Processing Beacons | | 360 | us |
| | Ramp Down | To Stand By 32.768KHz mode | | 760 | us |
| VHIO Supply | Input Supply Voltage | VHIO input supply determines Host CMOS logic levels | 1.7 | | 3.3 |
| | Input Supply Current | VHIO = 1.8V | | 1 | mA |
| | Standby Mode Current | VHIO = 1.8V | | 100 | uA |
| VLDO Supply | Input Supply Voltage | Required Internal regulator supply input | 1.45 | | 2.0 |
| Input Voltage Levels | VIL | | -0.3 | 0.25VHIO | V |
| | VIH | | 0.625VHIO | VHIO+0.3 | V |
| Output Voltage Levels | VOL | IOL = 8.0mA | | 0.4 | V |
| | VOH | IOH = -8.0mA | 0.75VHIO | VHIO | V |
| Input Capacitance | | | 1.0 | 5.0 | pF |
| | | | | | |



SG901-1071

RF Characteristics (Max and Min based on temperature range)

| Parameter | Test Condition / Comment | | Min. | Typ. | Max. | Units |
|-----------------------------------|--------------------------|------------------------|------|-------|------|-------|
| Antenna Port Impedance | | | | 50 | | Ohms |
| Antenna Input Return Loss | CH1 to CH14 | | -9.5 | | -14 | dB |
| RX Sensitivity | 11b, 1Mbps | | -97 | -96.3 | -95 | dBm |
| | 11b, 2 Mbps | | -94 | -93.5 | -91 | dBm |
| | 11b, 5.5 Mbps | | -93 | -91 | -88 | dBm |
| | 11b, 11 Mbps | | -89 | -86.7 | -85 | dBm |
| | 11g, 9Mbps | | -92 | -89.6 | -88 | dBm |
| | 11g, 18Mbps | | -87 | -85.9 | -84 | dBm |
| | 11g, 36Mbps | | -80 | -78.6 | -77 | dBm |
| | 11g, 54Mbps | | -74 | -72.4 | -70 | dBm |
| | 11n, MCS1 | | | -86 | | dBm |
| | 11n, MCS3 | | | -80 | | dBm |
| | 11n, MCS5 | | | -72 | | dBm |
| | 11n, MCS7 | | | -69 | | dBm |
| Channel to Channel De-sensitivity | CH1 to 14 | 11g, 54Mbps 10% PER | -0.7 | | 0.7 | dB |
| Maximum Input Signal | CH7 | 11g, 54Mbps | -19 | | -16 | dBm |
| Adjacent Channel Rejection | 1Mbps | | | 50 | | |
| | 11Mbps | | | 47 | | |
| | 9Mbps | | | 25 | | dB |
| | 54Mbps | | | 13 | | dB |
| | MCS1 | | | 24 | | dB |
| | MCS7 | | | 5 | | dB |
| TX Output Power | 11b, 1Mbps | @802.11b spectral mask | 15 | 16.5 | 19.1 | dBm |
| | 11b, 11Mbps | | 15.5 | 16.2 | 19.4 | dBm |
| | 11g, 9Mbps | @802.11g spectral mask | 17 | 18.2 | 19.5 | dBm |
| | 11g, 54Mbps | EVM = -27dB, 4.5% | 11.7 | 13.4 | 15.1 | dBm |
| | 802.11n MCS1 | @802.11n spectral mask | | 17 | | dBm |
| | 802.11n MCS7 | EVM = -27dB | | 13 | | dBm |



SG901-1071

Pinout List

| SIGNAL NAME | PIN NUMBER | DESCRIPTION | | NOTES |
|---|--|---|-------------|---|
| Reference Clock Pins | | | | |
| OSC_EN | 4 | Oscillator Enable Output | | not normally used – Contact Sagrad for options |
| REF_CLK | 19 | Reference Oscillator Input | | normally not connected - Contact Sagrad for options |
| RF Pins | | | | |
| BTH | 13 | Bluetooth RF Switched RF Connection | | RF Connection for Input - Output |
| 2G4_RF | 16 | Wi-Fi / Bluetooth Antenna Port, 50 ohms | | Careful RF design is needed for this and nearby ground |
| Serial Interface Pins (VHIO Domain, logic levels compatible with the VHIO (Pin 32) input voltage) | | | | |
| SDCMD | 25 | SPI MOSI (input) | SDIO CMD | VHIO Domain |
| SDCLK | 26 | SPI Clock Input | SDIO CLK | VHIO Domain |
| SDD0 | 24 | SPI MISO (output) | SDIO Data 0 | VHIO Domain |
| SDD1 | 23 | SPI: Interrupt Output | SDIO Data 1 | VHIO Domain |
| SDD2 | 22 | | SDIO Data 2 | VHIO Domain |
| SDD3 | 21 | SPI Chip Select Input | SDIO Data 3 | VHIO Domain |
| Control Pins | | | | |
| POWERUP | 5 | Power Up Enable (from Host) | | VLDO Domain with internal pull up High = operating, Low = off |
| RSTn | 31 | Reset Input | | VHIO Domain – Active Low reset |
| SLEEPCLK | 33 | 32.768 kHz Sleep Clock Input | | VHIO Domain |
| DBG_SPI_CSn | 27 | Debug SPI Chip Select Input | | VHIO Domain |
| DBG_SPI_CLK | 30 | Debug SPI Clock Input | | VHIO Domain |
| DBG_SPI_MISO | 28 | Debug SPI Data Output | | VHIO Domain |
| DBG_SPI莫斯 | 29 | Debug SPI Data Input | | VHIO Domain |
| Bluetooth Coexistence Pins (VHIO Domain) | | | | |
| WLAN_DENY | 1 | Bluetooth Coexistence | | VHIO Domain |
| BT_ACTIVE | 3 | Bluetooth Coexistence | | VHIO Domain |
| BT_PERIODIC | 2 | Bluetooth Coexistence | | VHIO Domain |
| BT_STATUS | 34 | Bluetooth Coexistence | | VHIO Domain |
| Power and Ground Pins | | | | |
| VHIO | 32 | Supply Voltage for I/O's | | 1.7 to 3.3V, Internally decoupled with a 0.1uF capacitor |
| VLDO | 6 | External regulator supply input | | 1.45 to 2.0V, Internally decoupled with a 2.4uF capacitor |
| 3.0V | 8 | RF supply | | 2.7 to 3.3V, Internally decoupled with a 0.2uF capacitor |
| GND | 7, 9, 10, 11, 12, 14, 15, 17, 18, 20, 35 | Ground Connections | | |



SG901-1071

Software Support

The 1071 and 1078 modules are supported through highly portable software. The hardware drivers and Wi-Fi stack as provided is compatible with Linux kernel 2.6. The source code for the hardware abstraction is available under a GPL license and is available from Sagrad. The licensed Wi-Fi licensed stack available from Sagrad is provided in binary form without a license. Source code for the Wi-Fi stack is available to the customer. To obtain source code for the stack contact Sagrad sales at www.sagrad.com. Software and source code are available free of charge but require a software license agreement for the Wi-Fi stack source.

In almost all cases the GPL driver will need to be modified for the customer's specific hardware. The Wi-Fi stack will only need to be modified for compatibility to the customers OS and compiler. In many cases such as Linux near zero modification of the Wi-Fi stack will be required.

The Wi-Fi module/stack currently is only tested in client mode and is compatible with any access point that meets 802.11 standards. An access point mode code base is planned in the future.

The complete 802.11 stack requires about 350KB of space for the implementation of the entire specification. Extremely small versions can be created by knowledgeable customers but is a considerable task and requires detailed understanding of 802.11.

As a service to customers, Sagrad offers extended technical support on a fee basis.



SG901-1071

Software Details:

MAC

- Comprehensive MAC functionality according to IEEE 802.11-2007, including QoS traffic scheduling
- Supports the following optional IEEE 802.11n features:
 - MPDU aggregation
 - MSDU aggregation
 - Immediate Block Acknowledgement
 - PSMP
 - MTBA
 - RIFS
 - L-SIG TXOP protection
- Link adaptation using MCS feedback

Encryption

- Hardware encryption according to IEEE 802.11-2007 and IEEE 802.11w/D10.0:
 - WEP40/64
 - WEP104/128
 - CCMP (AES)
 - TKIP
 - BIP
- Hardware encryption support for SMS4 to support WAPI
- Hardware encryption support for Cisco® CKIP


OS Support:

Windows Mobile 7 and 6.x, Windows CE 6.1 and 5, Linux v2.6, Android

Bluetooth Coexistence

| Feature | Linux |
|--------------------------------|-------|
| Bluetooth Coexistence | |
| PTA (802.15.2) | Yes |
| 802.11/BT on same Antenna | Yes |
| Data and Voice Simultaneously | Yes |
| Data and Data Simultaneously | Yes |
| Voice and Voice Simultaneously | Yes |

Recommended Layout




PCB design requires detailed review of the center exposed pad. This pad requires good thermal conductivity. Soldering coverage should be maximized and checked via x-ray for proper design. There is a trade off in providing enough solder for conductivity, and too much which allows the module to "float" on the paddle creating reliability issues. Sagrad recommends two approaches, a large center via that allows excess solder to flow down into the host PCB with smaller vias around it. Or many smaller vias with just enough space for the viscosity of the chosen solder/flux to allow some solder to flow into the smaller vias. Each of these approaches need to result in 60% or more full contact solder coverage on the paddle after reflow. Sagrad strongly encourages PCB layout teams to work with their EMS providers to insure vias and solder paste designs will result in satisfactory performance.

Note Pin one is on the bottom left of this diagram and is enlarged.

This view is viewed from the top.

Mechanical



The nominal size of the part is 10x13mm with a height of 1.7mm

Packaging

The part comes packaged in Tape and Reel or bulk.