



Poles	Dimensions			
	A		B	
02	.250	[6.35]	.550	[13.97]
03	.500	[12.70]	.800	[20.32]
04	.750	[19.05]	1.050	[26.67]
05	1.000	[25.40]	1.307	[33.20]
06	1.250	[31.75]	1.550	[39.37]
07	1.562	[38.10]	1.800	[45.72]
08	1.750	[44.45]	2.050	[52.07]
09	2.000	[50.80]	2.300	[58.42]
10	2.250	[57.15]	2.550	[64.77]

**SPECIFICATIONS:**  
 Material:  
 Insulator: Nylon 66, rated UL 94V-2  
 Insulator color: Natural  
 Contacts: Phosphor Bronze, Tin plated  
 Electrical:  
 Current rating: 02~10P: 12 Amp Max (With UL1015, 12AWG)  
 Contact resistance: 20 mohms max  
 Insulation resistance: 1,000M ohms min  
 Dielectric withstanding voltage: 2,900 VAC for 1 minute  
 Temperature Rating:  
 -40°C to +105°C  
 Environmental:  
 Lead free, RoHS compliant.



UNLESS OTHERWISE SPECIFIED ALL DIMENSIONS ARE MM [INCHES] TOLERANCES: EXCEPT AS NOTED INCHES                      HOLES .X     ± .10                    Ø.X     ± .10 .XX    ± .020                  Ø.XX    ± .015 .XXX   ± .015                  Ø.XXX   ± .010		
APPROVALS		DATE
DRAWN	LH	2/21/20
CHECKED	AY1	2/21/20
APPROVED		

909 Rahway Avenue,  
 Union, NJ 07083  
 Phone: 908-687-5000  
 Fax: 908-687-5710

TITLE		
WIRE TO BOARD, FEMALE, 6.35mm PITCH, WITH POLARIZING PEG, MALE PIN		
SIZE	PART NO.	REV.
X	DME-XX-S2-P-S	-
REF:	S00124T	SCALE: NTS
		SHEET 1 OF 1