


HT55AN103GN

Obsolete

HP LDD Indust COG HT200C, Ceramic, 0.01 uF, 2%, 25 VDC, COG, Commercial, High Temperature, Lead Spacing = 5.08mm



Click here for the 3D model.

Dimensions	
L	5.08mm MAX
Н	5.08mm MAX
Т	2.54mm MAX
S	5.08mm +/-0.762mm
LL	3.175mm MIN
F	0.635mm +0.102/-0.051mm
G	1.65mm MAX

Packagi	ng Specit	fications
---------	-----------	-----------

Packaging Waffle, Tray

General Information			
HP LDD Indust COG HT200C			
Radial			
Commercial, High Temperature			
LDD High Temperature 200C			
No			
▲ WARNING: Cancer and reproductive harm - http://www.p65warnings.ca.gov.			
Nickel			
No			

Specifications	
Capacitance	0.01 uF
Capacitance Tolerance	2%
Voltage DC	25 VDC
Temperature Range	-55/+200°C
Temperature Coefficient	COG

Statements of suitability for certain applications are based on our knowledge of typical operating conditions for such applications, but are not intended to constitute - and we specifically disclaim - any warranty concerning suitability for a specific customer application or use. This Information is intended for use only by customers who have the requisite experience and capability to determine the correct products for their application. Any technical advice inferred from this Information or otherwise provided by us with reference to the use of our products is given gratis, and we assume no obligation or liability for the advice given or results obtained.