

TTC-6-2XTVSD-12DC-PT - Surge protection device



2906807

<https://www.phoenixcontact.com/us/products/2906807>

Please be informed that the data shown in this PDF document is generated from our online catalog. Please find the complete data in the user documentation. Our general terms of use for downloads are valid.

Fine surge protection for two signal wires with common reference potential.



Your advantages

- Space-saving and cost-saving with a narrow overall width of just 6 mm
- Quick and tool-free installation of surge protective devices, thanks to Push-in connection technology
- Finding the right product for all possible requirements in MCR applications is easy, thanks to the complete range of products with customized features

Commercial data

Item number	2906807
Packing unit	1 pc
Minimum order quantity	1 pc
Sales key	CL23
Product key	CL2262
Catalog page	Page 148 (C-4-2019)
GTIN	4055626135717
Weight per piece (including packing)	31.2 g
Weight per piece (excluding packing)	25 g
Customs tariff number	85363010
Country of origin	DE

TTC-6-2XTVSD-12DC-PT - Surge protection device



2906807

<https://www.phoenixcontact.com/us/products/2906807>

Technical data

Product properties

IEC test classification	C1
	C2
	C3
Type	DIN rail module, one-piece
Product type	Surge protection for MCR technology
Product family	TERMITRAB complete

Insulation characteristics

Overvoltage category	III
Pollution degree	2

Electrical properties

Nominal voltage U_N	12 V DC
-----------------------	---------

Connection data

Connection method	Push-in connection
Conductor cross section flexible	0.2 mm ² ... 2.5 mm ²
Conductor cross section rigid	0.2 mm ² ... 4 mm ²
Conductor cross section AWG	24 ... 12

Dimensions

Dimensional drawing	
Width	6.2 mm +0.1 mm
Height	105.8 mm
Depth	69.5 mm (incl. DIN rail 7.5 mm)

Material specifications

Flammability rating according to UL 94	V-0
Insulating material	PBT
Housing material	PBT

Mechanical properties

Mechanical data

Open side panel	No
-----------------	----

Protective circuit

TTC-6-2XTVSD-12DC-PT - Surge protection device



2906807

<https://www.phoenixcontact.com/us/products/2906807>

Direction of action	Line-Earth Ground
Maximum continuous voltage U_C	15 V DC
	10 V AC
Rated current	6 A (55 °C)
Residual current I_{PE}	$\leq 200 \mu\text{A}$
Nominal discharge current I_n (8/20) μs (line-ground)	0.5 kA
Total discharge current I_{total} (8/20) μs	2 kA
Voltage protection level U_p (line-earth)	$\leq 35 \text{ V}$ (C1 - 1 kV / 500 A)
	$\leq 40 \text{ V}$ (C2 - 2 kV/1 kA)
	$\leq 25 \text{ V}$ (C3 - 25 A)
	$\leq 25 \text{ V}$ (C3 - 100 A)
Response time t_A (line-earth)	$\leq 1 \text{ ns}$
Input attenuation aE , asym.	typ. 0.3 dB ($\leq 130 \text{ kHz}/150 \Omega$)
Cut-off frequency f_g (3 dB), asym. (PE) in 150 Ω system	typ. 420 kHz
Capacity (Core-Earth)	typ. 5.2 nF
Resistance per path	$\leq 100 \text{ m}\Omega$
Surge protection fault message	none
Max. required back-up fuse	6.3 A (FF)
Impulse durability (line-earth)	C1 - 1 kV / 500 A
	C2 - 2 kV / 1 kA
	C3 - 100 A

Environmental and real-life conditions

Ambient conditions

Degree of protection	IP20
Ambient temperature (operation)	-40 °C ... 85 °C
Ambient temperature (storage/transport)	-40 °C ... 85 °C
Altitude	$\leq 4000 \text{ m}$ (amsl)
Permissible humidity (operation)	5 % ... 95 %

Standards and regulations

Standards/specifications	IEC 61643-21
Note	2000 + corrigendum 2001 + A1:2008, modified + A2:2012

EN 61643-21

Standards/specifications	EN 61643-21
Note	2001 + A1:2009 + A2:2013

Mounting

Mounting type	DIN rail: TH 35 - 7.5 mm
---------------	--------------------------

TTC-6-2XTVSD-12DC-PT - Surge protection device




2906807


<https://www.phoenixcontact.com/us/products/2906807>

Drawings

Circuit diagram



Diagram




TTC-6-2XTVSD-12DC-PT - Surge protection device

2906807

<https://www.phoenixcontact.com/us/products/2906807>



Dimensional drawing



TTC-6-2XTVSD-12DC-PT - Surge protection device



2906807

<https://www.phoenixcontact.com/us/products/2906807>

Approvals

To download certificates, visit the product detail page: <https://www.phoenixcontact.com/us/products/2906807>



CSA

Approval ID: 70136717



DNV GL

Approval ID: TAE000027G



UL Listed

Approval ID: FILE E 138168



CSAus

Approval ID: 70136717

UAE-RoHS

Approval ID: 22-06-16191

cCSAus

TTC-6-2XTVSD-12DC-PT - Surge protection device



2906807

<https://www.phoenixcontact.com/us/products/2906807>

Classifications

ECLASS

ECLASS-11.0	27130807
ECLASS-13.0	27171501

ETIM

ETIM 8.0	EC000943
----------	----------

UNSPSC

UNSPSC 21.0	39121600
-------------	----------

TTC-6-2XTVSD-12DC-PT - Surge protection device



2906807

<https://www.phoenixcontact.com/us/products/2906807>

Environmental product compliance

REACH SVHC	Lead 7439-92-1
China RoHS	Environmentally Friendly Use Period = 50 years
	For information on hazardous substances, refer to the manufacturer's declaration available under "Downloads"

TTC-6-2XTVSD-12DC-PT - Surge protection device



2906807

<https://www.phoenixcontact.com/us/products/2906807>

Accessories

ZBF 6 CUS - Zack Marker strip, flat

0825027

<https://www.phoenixcontact.com/us/products/0825027>



Zack Marker strip, flat, Strip, can be ordered: Strip, white, labeled according to customer specifications, mounting type: snap into flat marker groove, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

ZBF 6:UNBEDRUCKT - Zack Marker strip, flat

0808710

<https://www.phoenixcontact.com/us/products/0808710>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

TTC-6-2XTVSD-12DC-PT - Surge protection device



2906807

<https://www.phoenixcontact.com/us/products/2906807>

ZBF 6/WH-100:UNBEDRUCKT - Zack Marker strip, flat

0808736

<https://www.phoenixcontact.com/us/products/0808736>



Zack Marker strip, flat, Strip, white, unlabeled, can be labeled with: PLOTMARK, CMS-P1-PLOTTER, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 1000

ZBF 6,QR:FORTL.ZAHLEN - Zack Marker strip, flat

0808765

<https://www.phoenixcontact.com/us/products/0808765>



Zack Marker strip, flat, Strip, white, labeled, Printed vertically: consecutive numbers 1 ... 10, 11 ... 20, etc. up to 91 ... 100, mounting type: snapped, for terminal block width: 6.2 mm, lettering field size: 5.15 x 6.15 mm, Number of individual labels: 10

TTC-6-2XTVSD-12DC-PT - Surge protection device



2906807

<https://www.phoenixcontact.com/us/products/2906807>

CLIPFIX 35-5 - End clamp

3022276

<https://www.phoenixcontact.com/us/products/3022276>



Quick mounting end clamp for NS 35/7,5 DIN rail or NS 35/15 DIN rail, with marking option, with parking option for FBS...5, FBS...6, KSS 5, KSS 6, width: 5.15 mm, color: gray

SSA 3-6 - Shield connection

2839295

<https://www.phoenixcontact.com/us/products/2839295>



Shield fast connection for 3 ... 6 mm cable diameter. Potential connecting cable: 200 mm, 1 mm², color: black

TTC-6-2XTVSD-12DC-PT - Surge protection device



2906807

<https://www.phoenixcontact.com/us/products/2906807>

SSA 5-10 - Shield connection

2839512

<https://www.phoenixcontact.com/us/products/2839512>



Shield fast connection for 5 ... 10 mm cable diameter. Potential connecting cable: 200 mm, 1 mm², color: black

X-PEN 0,35 - Marker pen

0811228

<https://www.phoenixcontact.com/us/products/0811228>



Marker pen without ink cartridge, for manual labeling of markers, labeling extremely wipe-proof, line thickness 0.35 mm

Phoenix Contact 2023 © - all rights reserved
<https://www.phoenixcontact.com>

Phoenix Contact USA
586 Fulling Mill Road
Middletown, PA 17057, United States
(+717) 944-1300
info@phoenixcon.com