


Ø4.76

[Ø.19]

SCREW

BOTTOM VIEW

35.00 [1.38]



Enclosures can be Factory Modified (Milling, Drilling, Printing etc.)
Contact Factory (modshop@hammfg.com) for quotes Solid models of this enclosure available in .stp or .x_t (Part number and text placement/orientation on our products are subject to change, we do not recommend using them as a locating reference for modification purposes)

NOTE

Purchased assembly includes box, lid, gasket, 4 cover screws. Polycarbonate material is rated UL94 - V0

Recommended Torque: #4 Cover screw (71-100) Ozf.in / (50-70) cN.m Recommended Torque: #2 Internal screws (21-28) Ozf.in / (15-20) cN.m

| | PART NUMBERS 1551WH Enclosure | |
|-----------------|---|----------------------|
| | | |
| | Polycarbonate Black Enclosure | 1551WHBK |
| | Polycarbonate Gray Enclosure | 1551WHGY |
| | ACCESSORIES | |
| | Internal Mounting Post Screw [#2 x 3/16" Plastite Self-tapping (4.8mm)] | 1553WTS100 (Pkg 100) |
| | Stainless Steel Cover Screws [#4 X 3/8" Plastite Self-tapping (9.5mm)] | SC509-50 (Pkg 50) |
| R4.42 [R.17] | HAMMOND | |



Dimensions:

[.38]

[Ø.10]

mm [inches]

MAXIUMUM

P.C. BOARD

4.75

[.19]

www.hammondmfg.com