



**ALPHA & OMEGA**  
SEMICONDUCTOR

**AON1606**

**20V N-Channel MOSFET**

### General Description


The AON1606 utilize advanced trench MOSFET technology in small DFN 1.0 x 0.6 package. This device is ideal for load switch applications.

### Product Summary

$V_{DS}$	20V
$I_D$ (at $V_{GS}=4.5V$ )	0.7A
$R_{DS(ON)}$ (at $V_{GS}=4.5V$ )	< 275mΩ
$R_{DS(ON)}$ (at $V_{GS}=2.5V$ )	< 335mΩ
$R_{DS(ON)}$ (at $V_{GS}=1.8V$ )	< 390mΩ

Typical ESD protection

HBM Class 1C



### Absolute Maximum Ratings $T_A=25^\circ C$ unless otherwise noted

Parameter	Symbol	Maximum	Units
Drain-Source Voltage	$V_{DS}$	20	V
Gate-Source Voltage	$V_{GS}$	$\pm 8$	V
Continuous Drain Current <sup>E</sup>	$I_D$	0.7	A
$T_A=70^\circ C$		0.55	
Pulsed Drain Current <sup>C</sup>	$I_{DM}$	2.8	A
Power Dissipation <sup>A</sup>	$P_D$	0.9	W
$T_A=70^\circ C$		0.55	
Junction and Storage Temperature Range	$T_J, T_{STG}$	-55 to 150	°C

### Thermal Characteristics

Parameter	Symbol	Typ	Max	Units
Maximum Junction-to-Ambient <sup>A</sup>	$R_{\theta JA}$	80	100	°C/W
Steady-State		110	140	°C/W
Maximum Junction-to-Ambient <sup>B</sup>	$R_{\theta JA}$	200	245	°C/W
Steady-State		280	340	°C/W

**Electrical Characteristics ( $T_J=25^\circ\text{C}$  unless otherwise noted)**

Symbol	Parameter	Conditions	Min	Typ	Max	Units
<b>STATIC PARAMETERS</b>						
$BV_{DSS}$	Drain-Source Breakdown Voltage	$I_D=250\mu\text{A}, V_{GS}=0\text{V}$	20			V
$I_{DSS}$	Zero Gate Voltage Drain Current	$V_{DS}=20\text{V}, V_{GS}=0\text{V}$ $T_J=55^\circ\text{C}$			1 5	$\mu\text{A}$
$I_{GSS}$	Gate-Body leakage current	$V_{DS}=0\text{V}, V_{GS}=\pm 8\text{V}$			$\pm 10$	$\mu\text{A}$
$V_{GS(\text{th})}$	Gate Threshold Voltage	$V_{DS}=V_{GS}, I_D=250\mu\text{A}$	0.3	0.65	1.0	V
$I_{D(\text{ON})}$	On state drain current	$V_{GS}=4.5\text{V}, V_{DS}=5\text{V}$	2.8			A
$R_{DS(\text{ON})}$	Static Drain-Source On-Resistance	$V_{GS}=4.5\text{V}, I_D=0.4\text{A}$ $T_J=125^\circ\text{C}$	225	275		$\text{m}\Omega$
		$V_{GS}=2.5\text{V}, I_D=0.3\text{A}$	313	380		$\text{m}\Omega$
		$V_{GS}=1.8\text{V}, I_D=0.2\text{A}$	265	335		$\text{m}\Omega$
		$V_{GS}=1.5\text{V}, I_D=0.1\text{A}$	300	390		$\text{m}\Omega$
$g_{FS}$	Forward Transconductance	$V_{DS}=5\text{V}, I_D=0.4\text{A}$	355			$\text{S}$
$V_{SD}$	Diode Forward Voltage	$I_S=0.4\text{A}, V_{GS}=0\text{V}$	2	0.75	1.2	V
$I_S$	Maximum Body-Diode Continuous Current <sup>E</sup>				-0.7	A
<b>DYNAMIC PARAMETERS</b>						
$C_{iss}$	Input Capacitance	$V_{GS}=0\text{V}, V_{DS}=10\text{V}, f=1\text{MHz}$	62.5			pF
$C_{oss}$	Output Capacitance		12.5			pF
$C_{rss}$	Reverse Transfer Capacitance		9			pF
$R_g$	Gate resistance	$V_{GS}=0\text{V}, V_{DS}=0\text{V}, f=1\text{MHz}$	5.5			$\Omega$
<b>SWITCHING PARAMETERS</b>						
$Q_g$	Total Gate Charge	$V_{GS}=4.5\text{V}, V_{DS}=10\text{V}, I_D=0.4\text{A}$	0.85			nC
$Q_{gs}$	Gate Source Charge		0.1			nC
$Q_{gd}$	Gate Drain Charge		0.25			nC
$t_{D(\text{on})}$	Turn-On Delay Time	$V_{GS}=4.5\text{V}, V_{DS}=10\text{V}, R_L=25\Omega, R_{\text{GEN}}=3\Omega$	2			ns
$t_r$	Turn-On Rise Time		4			ns
$t_{D(\text{off})}$	Turn-Off Delay Time		18			ns
$t_f$	Turn-Off Fall Time		8			ns

A: The value of  $R_{\text{QJA}}$  is measured with the device mounted on 1in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The Power dissipation  $P_{\text{DSM}}$  is based on  $R_{\text{QJA}}$  and the maximum allowed junction temperature of 150° C. The value in any given application depends on the user's specific board design, and the maximum temperature of 150° C may be used if the PCB allows it to.







B: The value of  $R_{\text{QJA}}$  is measured with the device mounted on FR-4 minimum pad board, in a still air environment with  $T_A=25^\circ\text{C}$ . The Power dissipation  $P_{\text{DSM}}$  is based on  $R_{\text{QJA}}$  and the maximum allowed junction temperature of 150° C. The value in any given application depends on the user's specific board design, and the maximum temperature of 150° C may be used if the PCB allows it to.






C: The static characteristics in Figures 1 to 6 are obtained using <300  $\mu\text{s}$  pulses, duty cycle 0.5% max.


D: These tests are performed with the device mounted on 1 in<sup>2</sup> FR-4 board with 2oz. Copper, in a still air environment with  $T_A=25^\circ\text{C}$ . The SOA curve provides a single pulse rating.

E: The maximum current limited by package.

THIS PRODUCT HAS BEEN DESIGNED AND QUALIFIED FOR THE CONSUMER MARKET. APPLICATIONS OR USES AS CRITICAL COMPONENTS IN LIFE SUPPORT DEVICES OR SYSTEMS ARE NOT AUTHORIZED. AOS DOES NOT ASSUME ANY LIABILITY ARISING OUT OF SUCH APPLICATIONS OR USES OF ITS PRODUCTS. AOS RESERVES THE RIGHT TO IMPROVE PRODUCT DESIGN, FUNCTIONS AND RELIABILITY WITHOUT NOTICE.

**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**

**Fig 1: On-Region Characteristics (Note E)**

**Figure 2: Transfer Characteristics (Note E)**

**Figure 3: On-Resistance vs. Drain Current and Gate Voltage (Note E)**

**Figure 4: On-Resistance vs. Junction Temperature (Note E)**

**Figure 5: On-Resistance vs. Gate-Source Voltage (Note E)**

**Figure 6: Body-Diode Characteristics (Note E)**

**TYPICAL ELECTRICAL AND THERMAL CHARACTERISTICS**

**Figure 7: Gate-Charge Characteristics**

**Figure 8: Capacitance Characteristics**

**Figure 9: Maximum Forward Biased Safe Operating Area (Note B)**

**Figure 10: Single Pulse Power Rating Junction-to-Ambient (Note B)**

**Figure 11: Normalized Maximum Transient Thermal Impedance (Note B)**

**Gate Charge Test Circuit & Waveform**

**Resistive Switching Test Circuit & Waveforms**
