ITEM NO.	PART NUMBER	DESCRIPTION	QTY.	COMPONENT NOTES
1	50-00261	Connector, dc plug, 5.5x2.1xL20.5mm, brass nickel plated	1	
2	30-00689	Wire, 2C TS, 22 AWG, UL2464, 300V, 80C, 4.3 mm, VW-1, PVC	1	
3	24-00161	Overmold, dc plug, twistlock, PVC	1	black



Notes:
Made to mate with cable assembly: 10-02932 and 10-02978

Functionally equivalent components may be substituted

Wiring Diagram	
50-00261	wire color
center	red
sleeve	black

Revision:	Date:	Description:
A	9/19/2018	Initial release

Prepared: AW Digitally signed by AW Date: 2018.10.24 10:09:07 -07'00'

Verified: JP Digitally signed by JP Date: 2018.10.24 10:13:15 -07'00'

Dimensions are in millimeters.
Tolerances:
X: ± 0.5 mm
X.X: ± 0.3 mm
X.XX: ± 0.05 mm

Notes:

RoHS compliant

Function test: no open, no short circuit, no intermittent

Description:

Cable, 915 mm, 5.5x2.1 mm 50-00261 dc plug twist lock to 5 mm tinned, 22 AWG, UL2464

TENSILITY

tel 1.541.323.3228 *800* 877.670.7118
fax 1.541.323.4202 *web* tensility.com

Size: A

Part number: 10-02931

Scale: 1:1

Sheet 1 of 1

To see a custom version of this cable assembly, call Tensility at 541-323-3228 or email engineering@tensility.com